

SAHCO

1831



Balboa

Type: Upholstery

In accordance with California Bill AB 2998 and similar legislation within the United States, this product may not be used as upholstery. It can be used for vertical applications.

Composition: 100% polyester FR

Yarn type: Filament

Binding: Velvet

Width: Approx. 140 cm, 55 inches

Weight: Approx. 960 g/lin.m, 31 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week.

Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary.

Extraction cleaning might dissolve water based glue. Pay attention to temperature and amount of cleaning fluid.

Velour/chenille fabrics should be vacuumed in the nap direction.

Disinfection, see www.kvadrat.dk/en/sahco

1/30/ X X 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

10 year warranty



Abrasion

Approx. 100.000 Martindale rubs, EN ISO 12947

Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention

Pilling

Note 4, EN ISO 12945

Seam slippage

Seam parallel to warp: 2.0 mm, parallel to weft: 2.0 mm
EN ISO 13 936-2 180 Newton

Lightfastness

Note 4-6 ISO 105-B02

Fastness to rubbing

Dry note 4-5 ISO 105-X12

Wet note 3-5 ISO 105-X12

Absorption

0.50/Class D (flat), 0.80/Class B (waved) EN ISO 354

Airflow

7386 Pa s/m EN 29053

SAHCO

1831

Flame resistance

ASTM E84 Class A Unadhered
AS/NZS 1530.3
AS/NZS 3837 class 1
BS 5852 Crib 5
BS 5867 part 2 type B
CAN ULC S102
CAN ULC S109
DIN 4102 B1
EN 1021-1/2
EN 13501-1, B-s1, do
EN 13 773 class 1
GB 8624 B1
IMO FTP Code 2010:Part 8
NF P 92 507 M1
NFPA 260
NFPA 701
SN 198 898 5.2
UNI 9175 11M
US Cal. Bull. 117-2013

ACT Guidelines Woven fabrics

Flammability

US Cal. Bull. 117-2013

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 4.5

Wet Crocking: Grade 4.5

Colour Fastness to Light AATCC 16

Grade 4.0 minimum 40 hours

Physical properties

Pilling Class 4 ASTM D4970

Breaking Strength warp 116 / weft 214 lbs, ASTM D5034

Seam Slippage warp 100 / weft 120 lbs, ASTM D4034

Abrasion ASTM D4966

100.000 cycles Martaindale – High Traffic

Quality benefits

Complies with Möbelfakta
Very good abrasion
Very good lightfastness
Permanent flame retardant
Washable

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions
No use of halogen based flame retardants (incl. brominated and chlorinated)
REACH compliant
Californian Proposition 65 list compliant
LBC Red list compliant

Green building certificates

Greenguard Gold: Low chemical emission
Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Italy

Launch

2018

Warranty

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information

www.kvadrat.dk/en/sahco