

Investigation report

contact Detlef von Seyfried SAHCO GmbH

department Laboratory Kreuzburger Str. 17-19

+49 (0) 52 1 / 543 - 498 phone

DE 90471 Nürnberg e-mail detlef.vonseyfried@delcotex.de

> 19.10.2022 date

investigation report No. 21/3397_2

order description: Assessment of the ignitability of upholstered furniture - cigarette test - according to

DIN EN 1021-1 (2014-10)

Assessment of the ignitability of upholstered furniture match flame test – according to DIN EN 1021-2 (2014-10)

Assessment of the ignitability of upholstered furniture – cigarette test –

according to BS 5852 source 0 (2006-03) - Clause 11

in accordance with BS 5852 Part 1 source 0 (1979) - Clause 11 The Furniture and Furnishings (Fire) (Safety) Regulations 1988 ACC. TO SHEDULE 4 PART I CIGARETTE TEST FOR VISIBLE PARTS Assessment of the ignitability of upholstered furniture – match flame test

according to BS 5852 source 1 (2006-03) - 20 sec. - Clause 11 in accordance with BS 5852 Part 1 source 0 (1979) - Clause 11 The Furniture and Furnishings (Fire) (Safety) Regulations 1988 ACC. TO SHEDULE 5 PART I MATCH TEST FOR VISIBLE PARTS

article "600751 Ecriture" test samples:

by the client sampling: orderer: see address date of order: 03.09.2021 receipt of order: 06.09.2021 date of testing: 23.09.2021

Remark: The results are valid only for the tested object. The accreditation applies for the methods listed in the annex to the certificate D-PL-17323-01-00. Accredited test methods are underlined. The valuations and Interpretations in the investigation report are not subject to accreditation. Tests conducted through co-operation partners are marked with o. All information provided by the customer, which is taken over unchecked and thus reflected in the examination report, are placed in quotation marks on the first page of the investigation report. The content of this investigation report will not be passed to third persons without written approval of the orderer. The partial publication of the test report, as well as the usage for commercial process, is only allowed with a permission of the DELCOTEX Delius Techtex GmbH & Co. KG. Remnants of test material will be destroyed after 3 months. Previously stated specifications / data sheets / certificates are only characters and no warranties. Also no warranty in case of durability will be overtaken. Finally our general delivery and payment conditions are valid (please see www.textillabor.eu).



Commerzbank AG Bielefeld ► IBAN DE58 4804 0035 0780 8900 00 ► BIC COBADEFFXXX



instructions for performing

method: Assessment of the ignitability of upholstered furniture – cigarette test –

according to DIN EN 1021-1 (2014-10)

measuring conditions:

test temperature: 20 +/- 2 °C test humidity: 65 +/- 4 % room temperature: 22,3°C yes

foam: normal flammability foam 22-24 kg/m³

test results

article "600751 Ecriture"

Smouldering criteria:	cigarette 1	cigarette 2	cigarette 3
Unsafe escalating combustion	no	no	no
Test assembly consumed	no	no	no
Smoulders to extremeties	no	no	no
Smoulders through thickness	no	no	no
Smoulders more than 1 hour	no	no	no
In final examination, presence of active smouldering	no	no	no
Flaming criteria:			
Occurence of flames	no	no	no
Cigarette behaviour:			
self-extinguishment of cigarette	yes	yes	yes
Burning time (min.:sec.)	02:43	14:55	28:46

Result:	no ignition
---------	-------------



instructions for performing

method: Assessment of the ignitability of upholstered furniture –

match flame test – according to DIN EN 1021-2 (2014-10)

measuring conditions:

test temperature: 20 +/- 2 °C test humidity: 65 +/- 4 % room temperature: 23,1°C yes

foam: normal flammability foam 22-24 kg/m³

test results

article "600751 Ecriture"

Smouldering criteria:	Test 1	Test 2	Test 3
Unsafe escalating combustion	no	no	no
Test assembly consumed	no	no	no
Smoulders to extremeties	no	no	no
Smoulders through thickness	no	no	no
Smoulders more than 1 hour	no	no	no
In the final examination, presence of active smouldering	no	no	no
Flaming criteria:			
Unsafe escalating combustion	no	no	no
Test assembly consumed	no	no	no
Flames to extremeties	no	no	no
Flames through thickness	no	no	no
Flames longer than 120sec.	no	no	no

Result:	no ignition



instructions for performing

method: Assessment of the ignitability of upholstered furniture — cigarette test — according to BS 5852 source 0 (2006-03) — Clause 11

in accordance with BS 5852 Part 1 source 0 (1979) - Clause 11 The Furniture and Furnishings (Fire) (Safety) Regulations 1988 ACC. TO SHEDULE 4 PART I CIGARETTE TEST FOR VISIBLE PARTS

measuring conditions:

test temperature: 20 +/- 2 °C test humidity: 65 +/- 4 % 22,5°C room temperature: yes watersoak:

normal flammability foam 22 kg/m³ foam:

test results

article "600751 Ecriture"

Smouldering criteria:	Cigarette 1	Cigarette 2
Unsafe escalating combustion	no	no
Test assembly consumed	no	no
Smoulders to extremeties	no	no
Smoulders through thickness	no	no
Smoulders more than 1 hour	no	no
In the final examination, presence of active smouldering	no	no
Flaming criteria:		
Unsafe escalating combustion	no	no
Test assembly consumed	no	no
Flames to extremeties	no	no
Flames through thickness	no	no
Occurence of flames	no	no
Cigarette behaviour:		
self-extinguishment of cigarette	yes	yes
Burning time [min:sec]	08:44	24:48
Beschädigter Bereich - Extent of damage		
Vertical component width/depth (mm)	12/0	52/1
Horizontal component length/width/depth (mm)	8/13/0	13/49/1

Result:	no ignition NIO	



instructions for performing

method:Assessment of the ignitability of upholstered furniture – match flame testaccording to BS 5852 source 1 (2006-03) – 20 sec. – Clause 11

according to BS 5852 source 1 (2006-03) – 20 sec. – Clause 11 in accordance with BS 5852 Part 1 source 0 (1979) - Clause 11 The Furniture and Furnishings (Fire) (Safety) Regulations 1988 ACC. TO SHEDULE 5 PART I MATCH TEST FOR VISIBLE PARTS

measuring conditions:

test temperature:20 + /- 2 °Ctest humidity:65 + /- 4 %room temperature:21,7°Cwatersoak:yes

foam: normal flammability foam 22 kg/m³

test results

article "600751 Ecriture"

	Versuch 1	Versuch 2
Smouldering criteria:	Test 1	Test 2
Unsafe escalating combustion	no	no
Test assembly consumed	no	no
Smoulders to extremeties	no	no
Smoulders through thickness	no	no
Smoulders more than 1 hour	no	no
In the final examination, presence of active smouldering	no	no
Flaming criteria:		
Unsafe escalating combustion	no	no
Test assembly consumed	no	no
Flames to extremeties	no	no
Flames through thickness	no	no
Flames longer than 120 sec	no	no
Duration of Ignition source [min:sec]	00:00	00:00
Duration of flames [min:sec]	00:21	00:22
Duration of smoke [min:sec]	00:23	00:24
Extent of damage		
Vertical component width/depth (mm)	21/1	19/1
Horizontal component length/width/depth (mm)	7/16/0	9/14/0

Result:	No ignition NI1
Result:	No ignition NI1



test results

article "600751 Ecriture"

weight: 712,28 g/m², thickness: 2,17 mm

Remark:

The above test results relate only to the ignitability of the combination of materials under the particular condition of the test; they are not intended as a means of assessing the full potential fire hazard of the materials in use

i.A. Detlef von Seyfried

Laboratory

DELCOTEX Delius Techtex GmbH & Co. KG

Only the information in the signed test report is considered as binding.



attachment

article "600751 Ecriture"

<u>assessment of the ignitability of upholstered furniture – cigarette test – according to DIN EN 1021-1 (2014-10)</u>



<u>Assessment of the ignitability of upholstered furniture – match flame test – according to DIN EN 1021-2 (2014-10)</u>





attachment

article "600751 Ecriture"

<u>Assessment of the ignitability of upholstered furniture – cigarette test – according to BS 5852 source 0 (2006-03) - Clause 11</u>



Assessment of the ignitability of upholstered furniture — match flame test according to BS 5852 source 1 (2006-03) — 20 sec. — Clause 11

