





Nara

Type: Upholstery

Composition: 50% linen, 35% cotton, 15% viscose

Yarn type: Staple / Filament Binding: Chenille / Dobby

Width: Approx. 140 cm, 55 inches Weight: Approx. 1010 g/lin.m, 33 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week.

Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary.

Extraction cleaning might dissolve water based glue. Pay attention to temperature and amount of cleaning fluid.

Velour/chenille fabrics should be vacuumed in the nap direction.

Disinfection, see www.kvadrat.dk/en/sahco







Abrasion

Approx. 60.000 Martindale rubs, EN ISO 12947

Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention

Pilling

Note 5, EN ISO 12945

Seam slippage

Seam parallel to warp: 1.0 mm, parallel to weft: 2.0 mm EN ISO 13 936-2 180 Newton

Lightfastness

Note 5-6 ISO 105-B02

Fastness to rubbing

Dry note 4 ISO 105-X12 Wet note 3-4 ISO 105-X12

Flame resistance

BS 5852 Crib 5 with treatment *
BS 5852 Part 1
EN 1021-1/2
IMO FTP Code 2010:Part 8
US Cal. Bull. 117-2013 with Cal. 117 compliant interliner

* To pass this test flame retardant treatment is necessary. We are looking into more environmental friendly alternatives but for now the external finisher may use a treatment containing halogen based flame retardants.



ACT Guidelines Woven fabrics

Flammability

US Cal. Bull. 117-2013 with Cal. 117 compliant interliner

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 5.0 Wet Crocking: Grade 4.0

Colour Fastness to Light AATCC 16

Grade 4.5 minimum 40 hours

Physical properties

Pilling ASTM D3511 Class 5 Breaking Strength ASTM D5034 warp 77 / weft 64 lbs Seam Slippage ASTM D4034 warp 85.5 / weft 82.5 lbs

Abrasion ASTM D4966

60.000 cycles Martaindale - High Traffic

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

No use of halogen based flame retardants (incl. brominated and chlorinated)

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Green building certificates

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile
content and substance

Country of origin

Italy

Launch

2020

Warranty

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information

www.kvadrat.dk/en/sahco