
Apo Colour 101 Design: Ronan and Erwan Bouroullec



Product description

Apo by Ronan and Erwan Bouroullec has an elegant woven look and an aluminium backing. Slightly transparent, it provides a high degree of control over glare while reducing the need for cooling systems and the associated energy consumption.

Application: Roller blind Composition: 100% Trevira CS, aluminium backing Openness factor: 2%

Width: 240 cm (94,5 inches) Weight: 210 g/m² Thickness: 0.40 mm

Warranty

The textile comes with a 5 years product guarantee and complies with all the relevant legislation, regulations and standards. Improper cleaning, outdoor use, treatment with chemically aggressive agents, and external influences (incl. damage, insects, polluted condensation) do not fall within the scope of the warranty.

Care

Please see the ISO symbols. Clean with a dry or moist wrung cloth. Only use clean water. Can also be brushed or carefully vacuumed (reduce suction power) with a brush nozzle. In case of considerable staining, we recommend contacting a professional dry cleaner.

Flame resistance

EN 13501-1 (B-s1, d0) BS 5867 Part 2 type B DIN 4102 B1 NFPA 701 GB 50222 B1 JIS L 1091 A-1 D EN 13773 Class 1 GB 8624 B1

Solar optical properties (EN 14500:2021)

Visual Light Transmission	6%
Solar Reflection	64%
Solar Absorption	30%

Thermal performance

(EN 14501:2021, based on referenc	e glazing G)
G-tot value (SHGC) in %:	15%
U-tot value in W/m2K:	0.76
Total Light Transmission:	5%

Classifications for Visual comfort (EN 14501:2021)

Glare control	Class 3
Visual contact with the outside	Class 2

Lightfastness

0	
Interior	7 (ISO105-B02)
Exterior	7 (ISO105-B02)

Color Rendering Index Ra: 100

Acoustics

Sound absorption α -W: 0.40 (Class D)


Sustainability

Certificates: GREENGUARD Gold STANDARD 100 Class IV by OEKO-TEX® Environmental Product Declaration (EPD) Health Product Declaration (HPD)





Apo Colour 131 Design: Ronan and Erwan Bouroullec



Product description

Apo by Ronan and Erwan Bouroullec has an elegant woven look and an aluminium backing. Slightly transparent, it provides a high degree of control over glare while reducing the need for cooling systems and the associated energy consumption.

Application: Roller blind Composition: 100% Trevira CS, aluminium backing Openness factor: 2%

Width: 240 cm (94,5 inches) Weight: 210 g/m² Thickness: 0.40 mm

Warranty

The textile comes with a 5 years product guarantee and complies with all the relevant legislation, regulations and standards. Improper cleaning, outdoor use, treatment with chemically aggressive agents, and external influences (incl. damage, insects, polluted condensation) do not fall within the scope of the warranty.

Care

Please see the ISO symbols. Clean with a dry or moist wrung cloth. Only use clean water. Can also be brushed or carefully vacuumed (reduce suction power) with a brush nozzle. In case of considerable staining, we recommend contacting a professional dry cleaner.



Flame resistance

EN 13501-1 (B-s1, d0) BS 5867 Part 2 type B DIN 4102 B1 NFPA 701 GB 50222 B1 JIS L 1091 A-1 D EN 13773 Class 1 GB 8624 B1

Solar optical properties (EN 14500:2021)

Visual Light Transmission	5%
Solar Reflection	64%
Solar Absorption	31%

Thermal performance

(EN 14501:2021, based on reference	ce glazing G)
G-tot value (SHGC) in %:	15%
U-tot value in W/m2K:	0.76
Total Light Transmission:	4%

Classifications for Visual comfort (EN 14501:2021)

Glare controlClass 4Visual contact with the outsideClass 2

Lightfastness

 Interior
 4-7 (ISO105-B02)

 Exterior
 7 (ISO105-B02)

Color Rendering Index Ra: 98

Acoustics


Sound absorption α -W: 0.40 (Class D)

Sustainability

Certificates: GREENGUARD Gold STANDARD 100 Class IV by OEKO-TEX® Environmental Product Declaration (EPD) Health Product Declaration (HPD)



Apo Colour 161 Design: Ronan and Erwan Bouroullec



Product description

Apo by Ronan and Erwan Bouroullec has an elegant woven look and an aluminium backing. Slightly transparent, it provides a high degree of control over glare while reducing the need for cooling systems and the associated energy consumption.

Application: Roller blind Composition: 100% Trevira CS, aluminium backing Openness factor: 2%

Width: 240 cm (94,5 inches) Weight: 210 g/m² Thickness: 0.40 mm

Warranty

The textile comes with a 5 years product guarantee and complies with all the relevant legislation, regulations and standards. Improper cleaning, outdoor use, treatment with chemically aggressive agents, and external influences (incl. damage, insects, polluted condensation) do not fall within the scope of the warranty.

Care

Please see the ISO symbols. Clean with a dry or moist wrung cloth. Only use clean water. Can also be brushed or carefully vacuumed (reduce suction power) with a brush nozzle. In case of considerable staining, we recommend contacting a professional dry cleaner.



Flame resistance

EN 13501-1 (B-s1, d0) BS 5867 Part 2 type B DIN 4102 B1 NFPA 701 GB 50222 B1 JIS L 1091 A-1 D EN 13773 Class 1 GB 8624 B1

Solar optical properties (EN 14500:2021)

Visual Light Transmission	4%
Solar Reflection	64%
Solar Absorption	31%

Thermal performance

(EN 14501:2021, based on reference	glazing G)
G-tot value (SHGC) in %:	15%
U-tot value in W/m2K:	0.76
Total Light Transmission:	3%

Classifications for Visual comfort (EN 14501:2021)

Glare controlClass 4Visual contact with the outsideClass 2

Lightfastness

 Interior
 4-7 (ISO105-B02)

 Exterior
 7 (ISO105-B02)

Color Rendering Index Ra: 98

Acoustics

Sound absorption α-W:0.40 (Class D)

Sustainability

Certificates: GREENGUARD Gold STANDARD 100 Class IV by OEKO-TEX® Environmental Product Declaration (EPD) Health Product Declaration (HPD)



Apo Colour 191 Design: Ronan and Erwan Bouroullec



Product description

Apo by Ronan and Erwan Bouroullec has an elegant woven look and an aluminium backing. Slightly transparent, it provides a high degree of control over glare while reducing the need for cooling systems and the associated energy consumption.

Application: Roller blind Composition: 100% Trevira CS, aluminium backing Openness factor: 2%

Width: 240 cm (94,5 inches) Weight: 210 g/m² Thickness: 0.40 mm

Warranty

The textile comes with a 5 years product guarantee and complies with all the relevant legislation, regulations and standards. Improper cleaning, outdoor use, treatment with chemically aggressive agents, and external influences (incl. damage, insects, polluted condensation) do not fall within the scope of the warranty.

Care

Please see the ISO symbols. Clean with a dry or moist wrung cloth. Only use clean water. Can also be brushed or carefully vacuumed (reduce suction power) with a brush nozzle. In case of considerable staining, we recommend contacting a professional dry cleaner.



Flame resistance

EN 13501-1 (B-s1, d0) BS 5867 Part 2 type B DIN 4102 B1 NFPA 701 GB 50222 B1 JIS L 1091 A-1 D EN 13773 Class 1 GB 8624 B1

Solar optical properties (EN 14500:2021)

Visual Light Transmission	4%
Solar Reflection	64%
Solar Absorption	31%

Thermal performance

(EN 14501:2021, based on reference	glazing G)
G-tot value (SHGC) in %:	15%
U-tot value in W/m2K:	0.76
Total Light Transmission:	3%

Classifications for Visual comfort (EN 14501:2021)

Glare controlClass 4Visual contact with the outsideClass 2

Lightfastness

 Interior
 4-5 (ISO105-B02)

 Exterior
 7 (ISO105-B02)

Color Rendering Index Ra: 98

Acoustics


Sound absorption α -W: 0.40 (Class D)

Sustainability

Certificates: GREENGUARD Gold STANDARD 100 Class IV by OEKO-TEX® Environmental Product Declaration (EPD) Health Product Declaration (HPD)



Apo Colour 201 Design: Ronan and Erwan Bouroullec



Product description

Apo by Ronan and Erwan Bouroullec has an elegant woven look and an aluminium backing. Slightly transparent, it provides a high degree of control over glare while reducing the need for cooling systems and the associated energy consumption.

Application: Roller blind Composition: 100% Trevira CS, aluminium backing Openness factor: 2%

Width: 240 cm (94,5 inches) Weight: 210 g/m² Thickness: 0.40 mm

Warranty

The textile comes with a 5 years product guarantee and complies with all the relevant legislation, regulations and standards. Improper cleaning, outdoor use, treatment with chemically aggressive agents, and external influences (incl. damage, insects, polluted condensation) do not fall within the scope of the warranty.

Care

Please see the ISO symbols. Clean with a dry or moist wrung cloth. Only use clean water. Can also be brushed or carefully vacuumed (reduce suction power) with a brush nozzle. In case of considerable staining, we recommend contacting a professional dry cleaner.



Flame resistance

EN 13501-1 (B-s1, d0) BS 5867 Part 2 type B DIN 4102 B1 NFPA 701 GB 50222 B1 JIS L 1091 A-1 D EN 13773 Class 1 GB 8624 B1

Solar optical properties (EN 14500:2021)

Visual Light Transmission	5%
Solar Reflection	64%
Solar Absorption	30%

Thermal performance

(EN 14501:2021, based on reference	e glazing G)
G-tot value (SHGC) in %:	15%
U-tot value in W/m2K:	0.76
Total Light Transmission:	4%

Classifications for Visual comfort (EN 14501:2021)

Glare controlClass 4Visual contact with the outsideClass 2

Lightfastness

 Interior
 4-7 (ISO105-B02)

 Exterior
 7 (ISO105-B02)

Color Rendering Index Ra: 98

Acoustics


Sound absorption α -W: 0.40 (Class D)

Sustainability

Certificates: GREENGUARD Gold STANDARD 100 Class IV by OEKO-TEX® Environmental Product Declaration (EPD) Health Product Declaration (HPD)



Apo Colour 431 Design: Ronan and Erwan Bouroullec



Product description

Apo by Ronan and Erwan Bouroullec has an elegant woven look and an aluminium backing. Slightly transparent, it provides a high degree of control over glare while reducing the need for cooling systems and the associated energy consumption.

Application: Roller blind Composition: 100% Trevira CS, aluminium backing Openness factor: 2%

Width: 240 cm (94,5 inches) Weight: 210 g/m² Thickness: 0.40 mm

Warranty

The textile comes with a 5 years product guarantee and complies with all the relevant legislation, regulations and standards. Improper cleaning, outdoor use, treatment with chemically aggressive agents, and external influences (incl. damage, insects, polluted condensation) do not fall within the scope of the warranty.

Care

Please see the ISO symbols. Clean with a dry or moist wrung cloth. Only use clean water. Can also be brushed or carefully vacuumed (reduce suction power) with a brush nozzle. In case of considerable staining, we recommend contacting a professional dry cleaner.



Flame resistance

EN 13501-1 (B-s1, d0) BS 5867 Part 2 type B DIN 4102 B1 NFPA 701 GB 50222 B1 JIS L 1091 A-1 D EN 13773 Class 1 GB 8624 B1

Solar optical properties (EN 14500:2021)

Visual Light Transmission	5%
Solar Reflection	64%
Solar Absorption	31%

Thermal performance

(EN 14501:2021, based on reference	e glazing G)
G-tot value (SHGC) in %:	15%
U-tot value in W/m2K:	0.76
Total Light Transmission:	4%

Classifications for Visual comfort (EN 14501:2021)

Glare controlClass 4Visual contact with the outsideClass 2

Lightfastness

 Interior
 4-7 (ISO105-B02)

 Exterior
 7 (ISO105-B02)

Color Rendering Index Ra: 91

Acoustics


Sound absorption α -W: 0.40 (Class D)

Sustainability

Certificates: GREENGUARD Gold STANDARD 100 Class IV by OEKO-TEX® Environmental Product Declaration (EPD) Health Product Declaration (HPD)



Apo Colour 601 Design: Ronan and Erwan Bouroullec



Product description

Apo by Ronan and Erwan Bouroullec has an elegant woven look and an aluminium backing. Slightly transparent, it provides a high degree of control over glare while reducing the need for cooling systems and the associated energy consumption.

Application: Roller blind Composition: 100% Trevira CS, aluminium backing Openness factor: 2%

Width: 240 cm (94,5 inches) Weight: 210 g/m² Thickness:0.40 mm

Warranty

The textile comes with a 5 years product guarantee and complies with all the relevant legislation, regulations and standards. Improper cleaning, outdoor use, treatment with chemically aggressive agents, and external influences (incl. damage, insects, polluted condensation) do not fall within the scope of the warranty.

Care

Please see the ISO symbols. Clean with a dry or moist wrung cloth. Only use clean water. Can also be brushed or carefully vacuumed (reduce suction power) with a brush nozzle. In case of considerable staining, we recommend contacting a professional dry cleaner.



Flame resistance

EN 13501-1 (B-s1, d0) BS 5867 Part 2 type B DIN 4102 B1 NFPA 701 GB 50222 B1 JIS L 1091 A-1 D EN 13773 Class 1 GB 8624 B1

Solar optical properties (EN 14500:2021)

Visual Light Transmission	5%
Solar Reflection	64%
Solar Absorption	31%

Thermal performance

(EN 14501:2021, based on referenc	e glazing G)
G-tot value (SHGC) in %:	15%
U-tot value in W/m2K:	0.76
Total Light Transmission:	4%

Classifications for Visual comfort (EN 14501:2021)

Glare control	Class 4
Visual contact with the outside	Class 2

Lightfastness

0	
Interior	7 (ISO105-B02)
Exterior	7 (ISO105-B02)

Color Rendering Index Ra: 98

Acoustics


Sound absorption α -W: 0.40 (Class D)

Sustainability

Certificates: GREENGUARD Gold STANDARD 100 Class IV by OEKO-TEX® Environmental Product Declaration (EPD) Health Product Declaration (HPD)



Apo Colour 701 Design: Ronan and Erwan Bouroullec



Product description

Apo by Ronan and Erwan Bouroullec has an elegant woven look and an aluminium backing. Slightly transparent, it provides a high degree of control over glare while reducing the need for cooling systems and the associated energy consumption.

Application: Roller blind Composition: 100% Trevira CS, aluminium backing Openness factor: 2%

Width: 240 cm (94,5 inches) Weight: 210 g/m² Thickness: 0.40 mm

Warranty

The textile comes with a 5 years product guarantee and complies with all the relevant legislation, regulations and standards. Improper cleaning, outdoor use, treatment with chemically aggressive agents, and external influences (incl. damage, insects, polluted condensation) do not fall within the scope of the warranty.

Care

Please see the ISO symbols. Clean with a dry or moist wrung cloth. Only use clean water. Can also be brushed or carefully vacuumed (reduce suction power) with a brush nozzle. In case of considerable staining, we recommend contacting a professional dry cleaner.



Flame resistance

EN 13501-1 (B-s1, d0) BS 5867 Part 2 type B DIN 4102 B1 NFPA 701 GB 50222 B1 JIS L 1091 A-1 D EN 13773 Class 1 GB 8624 B1

Solar optical properties (EN 14500:2021)

Visual Light Transmission	6%
Solar Reflection	64%
Solar Absorption	30%

Thermal performance

(EN 14501:2021, based on reference	glazing G)
G-tot value (SHGC) in %:	15%
U-tot value in W/m2K:	0.76
Total Light Transmission:	5%

Classifications for Visual comfort (EN 14501:2021)

Glare controlClass 4Visual contact with the outsideClass 2

Lightfastness

 Interior
 4-7 (ISO105-B02)

 Exterior
 7 (ISO105-B02)

Color Rendering Index Ra: 97

Acoustics

Sound absorption α -W: 0.40 (Class D)

Sustainability

Certificates: GREENGUARD Gold STANDARD 100 Class IV by OEKO-TEX® Environmental Product Declaration (EPD) Health Product Declaration (HPD)

