

Mori Design: Kinnasand

Type: Curtain Composition: 100% Trevira CS Yarn type: Staple Binding: Double leno weave Width: Approx. 325 cm, 128 inches Weight: Approx. 340 g/lin.m, 11 oz/ly Repeat: 34cm H

Colour difference may occur

Cleaning: Washing at max. 60°C. Drip drying. Shrinkage approx. 1% / 0% when washed at 60°C. Ironing might be necessary Disinfection, see www.kvadrat.dk

More info: Care and maintenance kvadrat.dk

 $\underline{\mathbb{W}} \boxtimes \boxtimes \overline{\mathbb{A}} \mathbb{P}$

 $2^{\text{year}}_{\text{warranty}}$



Mori

Lightfastness Note 7 ISO 105-B02

Flame resistance

ASTM E84 Class A Unadhered CAN ULC S102 CAN ULC S109 DIN 4102 B1 EN 13501-1, B-s1, d0 EN 13 773 class 1 GB 8624 B1 NF P 92 507 M1 NFPA 701

ACT Guidelines Woven fabrics

Flammability NFPA 701

Dry & Wet Crocking AATCC 8 Dry Crocking: Grade 5.0 Wet Crocking: Grade 5.0

Colour Fastness to Light AATCC 16 Grade 4.0 minimum 60 hours

Physical properties Seam Slippage ASTM D434 *Not required fabric under weight*

Quality benefits Very good lightfastness Permanent flame retardant Washable

Environmental benefits Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions No use of halogen-based flame retardants (incl. brominated and chlorinated) REACH compliant Californian Proposition 65 list compliant LBC Red list compliant Mono material designed for circularity Recyclable

kvadrat

Green Building certificates

Greenguard Gold: Low chemical emission Environmental Product Declaration (EPD): 3rd Party Verified. ISO 14025 & EN 15804. Developed in accordance with the European standard EN 15804+A2. Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Italy

Warranty

2 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information kvadrat.dk

kvadrat