



## Sone

### Abrasion

Approx. 40.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention*

### Pilling

Note 4-5, EN ISO 12945

### Seam slippage

Seam parallel to warp: 3.5 mm parallel to weft: 2.0 mm  
EN ISO 13 936-2 180 Newton

### Lightfastness

Note 5-7 ISO 105-B02

### Fastness to rubbing

Dry note 4-5 ISO 105-X12  
Wet note 4-5 ISO 105-X12

### Flame resistance

AS/NZS 3837 Class 1  
ASTM E84 Class A Adhered  
ASTM E84 Class A Unadhered  
BS 5852 Crib 5 with treatment \*  
BS 5852 Part 1 with treatment \*  
EN 1021-1/2  
IMO FTP Code 2010 Part 8  
SN 198 898 5.2 with treatment \*  
US Cal. Bull. 117-2013

*\* To pass this test flame retardant treatment is necessary.*

*We are looking into more environmentally friendly alternatives but for now the external finisher may use a treatment containing halogen based flame retardants.*

### ACT Guidelines Woven fabrics

### Flammability

US Cal. Bull. 117-2013

### Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 4.5  
Wet Crocking: Grade 4.5

### Colour Fastness to Light AATCC 16

Grade 4.0 minimum 40 hours

### Physical properties

Pilling Class 4-5 ASTM D4970  
Breaking Strength warp 329 / weft 343 lbs, ASTM D5034  
Seam Slippage warp 108.5 / weft 129 lbs, ASTM D4034

### Abrasion ASTM D4966

40.000 cycles Martindale – High Traffic / Public Spaces

### Sone

Design: Erwan & Ronan Bouroullec

Type: Upholstery

Composition: 100% post-consumer recycled polyester

Yarn type: Filament

Binding: Jacquard

Width: Approx. 140 cm, 55 inches

Weight: Approx. 570 g/lin.m, 18 oz/ly

Repeat: Approx. V. 49 cm, 19 inches, H. 49 cm, 19 inches

Colour difference may occur

*Cleaning: Vacuum clean frequently, ideally every week if fixed covers. Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water based glue. Pay attention to temperature and amount of cleaning fluid.*

*Also washable at 60-80°C, half wash load. Drip drying. Mount in moist condition. Shrinkage app. 2% at 60°C. Be aware of increased shrinking and creasing the higher the temperature.*

*Disinfection, see kvadrat.dk*

*More info: Care and maintenance kvadrat.dk*



10 year  
warranty



# kvadrat

**Quality benefits**

Complies with Möbelfakta  
Good lightfastness  
Flame retardant  
Washable

**Environmental benefits**

Follow the EU Ecolabel dye restrictions incl. AZO dye  
and heavy metal restrictions  
No use of halogen based flame retardants (incl. brominated  
and chlorinated)  
REACH compliant  
Californian Proposition 65 list compliant  
LBC Red list compliant  
Healthier Hospitals compliant  
No content of PFCs or 'PFAS'  
Mono-material designed for circularity  
Recyclable

**Green building certificates**

Greenguard Gold: Low chemical emission  
Environmental Product Declaration (EPD): Based on a LCA  
following EN 15804 and follow the standard of ISO 14040  
Health Product Declaration (HPD): Declaring textile content  
and substance

**Country of origin**

Holland/Netherlands

**Launch**

2023

**Warranty**

10 years. See terms and conditions on [kvadrat.dk](https://www.kvadrat.dk)

Kvadrat packaging and cardboard is recyclable. Cardboard  
material is FSC certified and / or contains recycled content.

For further information  
[kvadrat.dk](https://www.kvadrat.dk)