
Russell Colour 100

Design: Louise Sigvardt



Russell by Louise Sigvardt has an elegant, fine woven look. Constructed with a special white backing, it can deliver total darkness even if the outside daylight is powerful. Reflecting this, it meets the highest classification, the 100.000-lux test, and is ideal for rooms where blackout performance is desired. Simple collection including elegant, warm and cold neutrals.

Application: Roller blind

Composition: 100% polyester with acrylic

based block out coating Openness factor: 0%

Width: 300 cm (118 inches)

Weight: 420 g/m² Thickness: 0.6 mm

Warranty

The textile comes with a 5 years product guarantee and complies with all the relevant legislation, regulations and standards. Improper cleaning, outdoor use, treatment with chemically aggressive agents, and external influences (incl. damage, insects, polluted condensation) do not fall within the scope of the warranty.

Care

Please see the ISO symbols. Clean with a dry or moist wrung cloth. Only use clean water. Can also be brushed or carefully vacuumed (reduce suction power) with a brush nozzle. In case of considerable staining, we recommend contacting a professional dry cleaner.

Flame resistance

BS 5867 part 2 type B DIN 4102 B1 EN 13773 class 1 IMO FTP code 2010: part 7 NF P 92 507 M2 NFPA 701

Solar optical properties (EN 14500:2021)

Visual Light Transmission 0% Solar Reflection 73% Solar Absorption 27%

Thermal performance

(EN 14501:2021, based on reference glazing G)

G-tot value (SHGC) in %: 10%
Total Light Transmission: 0
U-value: 0.84

Classifications for Visual comfort (EN 14501:2021)

Glare control Class 4
Visual contact with the outside Class 0

Lightfastness

6-7 (ISO105-B02)

Sustainability

Certificates:

GREENGUARD Gold

Environmental Product Declaration (EPD)

Health Product Declaration (HPD)

PVC free










Russell Colour 120

Design: Louise Sigvardt



Product description

Russell by Louise Sigvardt has an elegant, fine woven look. Constructed with a special white backing, it can deliver total darkness even if the outside daylight is powerful. Reflecting this, it meets the highest classification, the 100.000-lux test, and is ideal for rooms where blackout performance is desired. Simple collection including elegant, warm and cold neutrals.

Application: Roller blind

Composition: 100% polyester with acrylic

based block out coating Openness factor: 0%

Width: 300 cm (118 inches)

Weight: 420 g/m² Thickness: 0.6 mm

Warranty

The textile comes with a 5 years product guarantee and complies with all the relevant legislation, regulations and standards. Improper cleaning, outdoor use, treatment with chemically aggressive agents, and external influences (incl. damage, insects, polluted condensation) do not fall within the scope of the warranty.

Care

Please see the ISO symbols. Clean with a dry or moist wrung cloth. Only use clean water. Can also be brushed or carefully vacuumed (reduce suction power) with a brush nozzle. In case of considerable staining, we recommend contacting a professional dry cleaner.

Flame resistance

BS 5867 part 2 type B DIN 4102 B1 EN 13773 class 1 IMO FTP code 2010: part 7 NF P 92 507 M2 NFPA 701

Solar optical properties (EN 14500:2021)

Visual Light Transmission 0% Solar Reflection 73% Solar Absorption 27%

Thermal performance

(EN 14501:2021, based on reference glazing G)

G-tot value (SHGC) in %: 10%
Total Light Transmission: 0
U-value: 0.84

Classifications for Visual comfort (EN 14501:2021)

Glare control Class 4
Visual contact with the outside Class 0

Lightfastness

6-7 (ISO105-B02)

Sustainability

Certificates:

GREENGUARD Gold

Environmental Product Declaration (EPD)

Health Product Declaration (HPD)

PVC free









Russell Colour 130

Design: Louise Sigvardt



Product description

Russell by Louise Sigvardt has an elegant, fine woven look. Constructed with a special white backing, it can deliver total darkness even if the outside daylight is powerful. Reflecting this, it meets the highest classification, the 100.000-lux test, and is ideal for rooms where blackout performance is desired. Simple collection including elegant, warm and cold neutrals.

Application: Roller blind

Composition: 100% polyester with acrylic

based block out coating Openness factor: 0%

Width: 300 cm (118 inches)

Weight: 420 g/m² Thickness: 0.6 mm

Warranty

The textile comes with a 5 years product guarantee and complies with all the relevant legislation, regulations and standards. Improper cleaning, outdoor use, treatment with chemically aggressive agents, and external influences (incl. damage, insects, polluted condensation) do not fall within the scope of the warranty.

Care

Please see the ISO symbols. Clean with a dry or moist wrung cloth. Only use clean water. Can also be brushed or carefully vacuumed (reduce suction power) with a brush nozzle. In case of considerable staining, we recommend contacting a professional dry cleaner.

Flame resistance

BS 5867 part 2 type B DIN 4102 B1 EN 13773 class 1 IMO FTP code 2010: part 7 NF P 92 507 M2 NFPA 701

Solar optical properties (EN 14500:2021)

Visual Light Transmission 0% Solar Reflection 73% Solar Absorption 27%

Thermal performance

(EN 14501:2021, based on reference glazing G)

G-tot value (SHGC) in %: 10%
Total Light Transmission: 0
U-value: 0.84

Classifications for Visual comfort (EN 14501:2021)

Glare control Class 4
Visual contact with the outside Class 0

Lightfastness

6-7 (ISO105-B02)

Sustainability

Certificates:

GREENGUARD Gold

Environmental Product Declaration (EPD)

Health Product Declaration (HPD)

PVC free










Russell Colour 200

Design: Louise Sigvardt



Product description

Russell by Louise Sigvardt has an elegant, fine woven look. Constructed with a special white backing, it can deliver total darkness even if the outside daylight is powerful. Reflecting this, it meets the highest classification, the 100.000-lux test, and is ideal for rooms where blackout performance is desired. Simple collection including elegant, warm and cold neutrals.

Application: Roller blind

Composition: 100% polyester with acrylic

based block out coating Openness factor: 0%

Width: 300 cm (118 inches)

Weight: 420 g/m² Thickness: 0.6 mm

Warranty

The textile comes with a 5 years product guarantee and complies with all the relevant legislation, regulations and standards. Improper cleaning, outdoor use, treatment with chemically aggressive agents, and external influences (incl. damage, insects, polluted condensation) do not fall within the scope of the warranty.

Care

Please see the ISO symbols. Clean with a dry or moist wrung cloth. Only use clean water. Can also be brushed or carefully vacuumed (reduce suction power) with a brush nozzle. In case of considerable staining, we recommend contacting a professional dry cleaner.

Flame resistance

BS 5867 part 2 type B DIN 4102 B1 EN 13773 class 1 IMO FTP code 2010: part 7 NF P 92 507 M2 NFPA 701

Solar optical properties (EN 14500:2021)

Visual Light Transmission 0% Solar Reflection 73% Solar Absorption 27%

Thermal performance

(EN 14501:2021, based on reference glazing G)

G-tot value (SHGC) in %: 10%
Total Light Transmission: 0
U-value: 0.84

Classifications for Visual comfort (EN 14501:2021)

Glare control Class 4
Visual contact with the outside Class 0

Lightfastness

6-7 (ISO105-B02)

Sustainability

Certificates:

GREENGUARD Gold

Environmental Product Declaration (EPD)

Health Product Declaration (HPD)

PVC free









Russell Colour 220

Design: Louise Sigvardt



Product description

Russell by Louise Sigvardt has an elegant, fine woven look. Constructed with a special white backing, it can deliver total darkness even if the outside daylight is powerful. Reflecting this, it meets the highest classification, the 100.000-lux test, and is ideal for rooms where blackout performance is desired. Simple collection including elegant, warm and cold neutrals.

Application: Roller blind

Composition: 100% polyester with acrylic

based block out coating Openness factor: 0%

Width: 300 cm (118 inches)

Weight: 420 g/m² Thickness: 0.6 mm

Warranty

The textile comes with a 5 years product guarantee and complies with all the relevant legislation, regulations and standards. Improper cleaning, outdoor use, treatment with chemically aggressive agents, and external influences (incl. damage, insects, polluted condensation) do not fall within the scope of the warranty.

Care

Please see the ISO symbols. Clean with a dry or moist wrung cloth. Only use clean water. Can also be brushed or carefully vacuumed (reduce suction power) with a brush nozzle. In case of considerable staining, we recommend contacting a professionaldry cleaner.

Flame resistance

BS 5867 part 2 type B DIN 4102 B1 EN 13773 class 1 IMO FTP code 2010: part 7 NF P 92 507 M2 NFPA 701

Solar optical properties (EN 14500:2021)

Visual Light Transmission 0% Solar Reflection 73% Solar Absorption 27%

Thermal performance

(EN 14501:2021, based on reference glazing G)

G-tot value (SHGC) in %: 10%
Total Light Transmission: 0
U-value: 0.84

Classifications for Visual comfort (EN 14501:2021)

Glare control Class 4
Visual contact with the outside Class 0

Lightfastness

6-7 (ISO105-B02)

Sustainability

Certificates:

GREENGUARD Gold

Environmental Product Declaration (EPD)

Health Product Declaration (HPD)

PVC free










Russell Colour 230

Design: Louise Sigvardt



Product description

Russell by Louise Sigvardt has an elegant, fine woven look. Constructed with a special white backing, it can deliver total darkness even if the outside daylight is powerful. Reflecting this, it meets the highest classification, the 100.000-lux test, and is ideal for rooms where blackout performance is desired. Simple collection including elegant, warm and cold neutrals.

Application: Roller blind

Composition: 100% polyester with acrylic

based block out coating Openness factor: 0%

Width: 300 cm (118 inches)

Weight: 420 g/m² Thickness: 0.6 mm

Warranty

The textile comes with a 5 years product guarantee and complies with all the relevant legislation, regulations and standards. Improper cleaning, outdoor use, treatment with chemically aggressive agents, and external influences (incl. damage, insects, polluted condensation) do not fall within the scope of the warranty.

Care

Please see the ISO symbols. Clean with a dry or moist wrung cloth. Only use clean water. Can also be brushed or carefully vacuumed (reduce suction power) with a brush nozzle. In case of considerable staining, we recommend contacting a professional dry cleaner.

Flame resistance

NFPA 701

BS 5867 part 2 type B DIN 4102 B1 EN 13773 class 1 IMO FTP code 2010: part 7 NF P 92 507 M2

Solar optical properties (EN 14500:2021)

Visual Light Transmission 0% Solar Reflection 73% Solar Absorption 27%

Thermal performance

(EN 14501:2021, based on reference glazing G)

G-tot value (SHGC) in %: 10%
Total Light Transmission: 0
U-value: 0.84

Classifications for Visual comfort (EN 14501:2021)

Glare control Class 4
Visual contact with the outside Class 0

Lightfastness

6-7 (ISO105-B02)

Sustainability

Certificates:

GREENGUARD Gold

Environmental Product Declaration (EPD)

Health Product Declaration (HPD)

PVC free







