

Test Certificate 105055 - 1

Report Details

Report Number 105055 - 1 Service Requested BS 5852 Part 1: 1979 - Schedule 4 Part 1 & Schedule 5

Date Recieved 15-Feb-23 Date Tested 20-Feb-23 Date Issued 20-Feb-23

Customer Details

Company Name FLAMENTEK LIMITED

Customer Contact JANE GIRLING Company Address COMPASS HOUSE

Customer Ref/PO 21986 BUNWELL ROAD BESTHORPE

NORFOLK

NR17 2NZ

Customer Details - As Supplied by the Customer

Sample Description CIFRADO - CHENILLE WOVEN FABRIC. TREATED WITH A DURAFLAM® FLAME RETARDANT FORMULATION BY

FABRIC FLARE SOLUTIONS LTD.

Fibre Composition 42% RECYCLED POLYESTER, 27% VISCOSE, 24% RECYCLED COTTON, 7% LINEN

Quality/Batch Ref CIFRADO

Colour VARIOUS

Sample End Use UPHOLSTERY

Model Ref Manufacturer

Supplier / Buyer KVADRAT A/S

Specification:

Schedule 4 Part 1 (The Cigarette test) and Schedule 5 Part 1 (The Match test) of The Furniture Furnishings (Fire) (Safety) Regulations 1988 (as amended). S.I. 1324.

Test Methods:

BS 5852 Part 1: 1979 – Methods of test for the ignitibility by smokers' materials of upholstered composites for seating.


Conditioning:

The sample was conditioned for 72 hrs in ambient conditions then for at least 24 hrs in a specified atmosphere at $20 \pm 5^{\circ}$ C and $50 \pm 20\%$ relative humidity.

Pre-Treatment:

Water soak procedure in accordance with BS 5651: 1978 - Clause 4 (as amended by The Furniture and Furnishings (Fire) (Safety) Regulations 1988

T: 0161 5050 650 E: technical@ifs-labs.com A: Textile Innovation House, 1 Lyons Road, Trafford Park, Manchester, M17 1RN





Page 1 of 3 2513



Test Certificate 105055 - 1

Test Results

The Following test results relate only to the ignitibility of the combination of the materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

Test Type	Schedule 4 Part 1	Initial Test	Repeat Test
Filling Material Used:		VP45 20-22Kg/m³	VP45 20-22Kg/m³
*Smouldering Duration [m	m:ss]:	FTS	FTS
*Progressive smouldering at the placement of the cigare	and/or flaming observed within one hour of ette:		
Evidence of melting:			
Evidence of charring:		•	✓
Evidence of dripping:			
Cover Split			
Forcibly Extinguished			
Test Result		PASS	PASS
Test Type	Schedule 5 Part 1	Initial Test	Repeat Test
Test Type Filling Material Used:	Schedule 5 Part 1	Initial Test VP45 20-22Kg/m³	Repeat Test VP45 20-22Kg/m³
			-
Filling Material Used: *Smouldering / Flaming / G		VP45 20-22Kg/m³	VP45 20-22Kg/m³
*Smouldering / Flaming / C *Progressive smouldering	Glowing Duration [mm:ss]:	VP45 20-22Kg/m³	VP45 20-22Kg/m³
*Smouldering / Flaming / C *Progressive smouldering the flame:	Glowing Duration [mm:ss]:	VP45 20-22Kg/m³ 0:00	VP45 20-22Kg/m³ 0:00
*Smouldering / Flaming / C *Progressive smouldering the flame: Evidence of melting:	Glowing Duration [mm:ss]:	VP45 20-22Kg/m³ 0:00 ✓	VP45 20-22Kg/m³ 0:00 ✓
*Smouldering / Flaming / C *Progressive smouldering the flame: Evidence of melting: Evidence of charring: Evidence of dripping:	Glowing Duration [mm:ss]:	VP45 20-22Kg/m³ 0:00 ✓	VP45 20-22Kg/m³ 0:00 ✓
*Smouldering / Flaming / C *Progressive smouldering the flame: Evidence of melting: Evidence of charring: Evidence of dripping: *Flaming continued for mo	Glowing Duration [mm:ss]: observed within one hour after the removal of	VP45 20-22Kg/m³ 0:00 ✓ ✓ ✓	VP45 20-22Kg/m³ 0:00 ✓

T: 0161 5050 650 E: technical@ifs-labs.com A: Textile Innovation House, 1 Lyons Road, Trafford Park, Manchester, M17 1RN

Copyright IFS Laboratories Limited



Page 2 of 3 2513



Test Certificate 105055 - 1

Overall Result: PASS

The sample supplied meets the UK Furniture and Furnishing (Fire)(Safety) Regulations 1988 (amended 1989, 1993, 2010) S.I.1324

Authorised Signature:


Zeb Alam

Operations Director

The uncertainty of measurement is taken into account when stating conformance to the specification. The test results are compared with the acceptance limits which are determined by reducing the specification limit by the expanded test uncertainty Uk=2 (approximately 95% confidence interval) and providing all measured values are within the tolerance limits then such results are declared as "Pass". The Uncertainty budgets are stated for each test method and should be considered when results are on or close to the acceptance limits, and in such cases it should be noted that the risk of false acceptance or false rejection is ≤2.5%. All test results issued on this report refer only to the item under test as supplied by the customer.

END OF REPORT

T: 0161 5050 650 E: technical@ifs-labs.com A: Textile Innovation House, 1 Lyons Road, Trafford Park, Manchester, M17 1RN





Page 3 of 3