Test Report

Report No.: A 909041-1

Kvadrat A/S

Attn.: Lone Henriksen

Assignor:



Gregersensvei DK-2630 Taastrup Tel. +45 72 20 20 00 Fax +45 72 20 20 19

info@teknologisk.dk www.teknologisk.dk

Page 1 of 1

Chf/leIn

Lundbergsvej 10 8400 Ebeltoft

Order no.: 909041 No. of appendices: 1

Subject: Upholstery fabric designated: Sunniva 3, Fibre content: 58 % new wool, 25 % viscose,

8% flax, 5 % nylon, 4 % polyester. (as per info from the assigner).



Sampling: The test material was sampled by the client and received at the Danish Technological In-

stitute 08.01.2020

Method: See Appendix 1.

Period: The testing was completed 16.01.2020

Result: Individual results appear from Appendix 1.

The test material will be destroyed after 6 months, unless otherwise agreed. Storage:

The accredited test was carried out according to DANAK's general conditions see www.danak.dk and according to Terms:

the General Terms and Conditions regarding Commissioned Work Accepted by the Danish Technological Institute, which apply at the time of signing the agreement. The test is only valid for the tested specimen. The test report

may only be extracted, if the laboratory has approved the extract.

Date/place: 17.01.2020, Danish Technological Institute, Wood and Biomaterials, Textile, Taastrup

Signature: Test responsible Co-signatory







A 909041-1

Report no.: Appendix: Page: 1 of 1 Initials: Chf/leIn

Test Methods	Results	
Abrasion resistance - Martindale	End-point:	>50 000 rubs
Part 2: Determination of specimen	Individual re-	>50 000 - >50 000 - >50 000 rubs
breakdown	sults:	
DS/EN ISO 12947-2:2016 Mass: 795 q	Colour change:	Note 4-5 after 6000 rubs
Nominal pressure: 12 kPa		
End-point: Two broken threads		
Colour change (1-5 scale, 5 best rating)		
ISO 105-A02:1993		
Test conditions: 21°C, 65%RH		