



Volume

Design: Kinnasand

Type: Curtain

Composition: 83% Trevira CS, 17% polyester FR

Yarn type: Filament

Binding: Dobby

Width: Approx. 300 cm, 118 inches

Weight: Approx. 320 g/m, 10 oz/y

Repeat: None

Colour difference may occur

Cleaning: Washing at max. 60°C.

Drip drying.

Shrinkage approx. 1% / 1% when washed at 60°C.

Ironing might be necessary.

Disinfection, see www.kvadrat.dk

More info: Care and maintenance [kvadrat.dk](http://www.kvadrat.dk)

60/ 

10 year
warranty



Volume

Lightfastness

Note 4-7 ISO 105-B02

Absorption

150 mm airgap

0.45/Class D (flat), 0.65/Class C (waved) EN ISO 354

100 mm airgap

0.40/Class D (flat), 0.55/Class D (waved) EN ISO 354

Airflow

356 Pa s/m EN 29053

Flame resistance

AS/NZS 1530.3

BS 5867 part 2 type B

DIN 4102 B1

EN 13 773 Class 1

IMO FTP Code 2010 Part 7

JIS L 1091 A-1 D

NF P 92 507 M1

NFPA 701

SN 198 898 5.1

UNI 9177 Classe 1

ACT Guidelines Woven fabrics

Flammability

NFPA 701

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 5.0

Wet Crocking: Grade 5.0

Physical properties

Seam Slippage warp 93.5 / weft 67.0 lbs. ASTM D434

Quality benefits

Permanent flame retardant

Washable

Benefits of Polyester FR

Polyester FR has hypoallergenic properties

Polyester FR dries fast

Polyester FR is inherently flame retardant so no additional chemical treatment is needed

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions
REACH compliant
Californian Proposition 65 list compliant
LBC Red list compliant
Mono material designed for circularity
Recyclable

Green Building certificates

Greenguard Gold: Low chemical emission
Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Switzerland

Launch

2023

Warranty

10 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information
kvadrat.dk