

Rumor Design: Bertjan Pot

Type: Upholstery

Composition: 21% new wool, 12% recycled polyester, 7% nylon, 60% recycled polyester filling Yarn type: Worsted Binding: Knit Width: approx. 165 cm, 65 inches Weight: approx. 1280 g/lin.m, 41 oz/ly Repeat: None

Colour difference may occur

Cleaning: Vacuuming gently. Washable at 30°C if loose covers. Drip drying. Shrinkage approx. 3% Mount in moist condition

More info: Care and maintenance kvadrat.dk

 $\underline{\mathbb{W}} \boxtimes \boxtimes \overline{\mathbb{A}} \mathbb{P}$



ý



Rumor

Abrasion

Approx. 100.000 Martindale rubs, EN ISO 12947

Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention

Pilling

Note 4-5, EN ISO 12945

Lightfastness Note 6-7, ISO 105-B02

Fastness to rubbing

Dry note 4-5, ISO 105-X12 Wet note 4, ISO 105-X12

Absorption

150 mm airgap 0.70/Class C (flat), EN ISO 354 100 mm airgap 0.60/Class C (flat), EN ISO 354

Airflow

360 Pa s/m EN 29035

Flame resistance

AS/NZS 3837 class 1 ASTM E84 Class A Unadhered BS 5852 part 1 ignition source 0 BS 5852 Crib 5, with treatment * EN 1021-1/2 IMO FTP Code 2010 part 8 UNI 9175 1IM US Cal. Bull. 117-2013

Free from added flame-retardant chemicals as standard

* To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants

kvadrat febrik

ACT Guidelines Knit fabrics

Flammability US Cal. Bull. 117-2013

Dry & Wet Crocking AATCC 8 Dry Crocking: Grade 5.0 Wet Crocking: Grade 4.0

Colour Fastness to Light AATCC 16 Grade 4.5 minimum 40 hours

Physical properties

Pilling Class 4-5 ASTM D4970 Breaking Strength warp 127 / weft 219 lbs, ASTM D5034 Seam Slippage warp 144 / weft 156 lbs, ASTM D4034

Abrasion

100.000 cycles Martindale – High Traffic / Public Space

Quality benefits

Great wear- and stretchability Very good abrasion Good lightfastness Flame retardant

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions REACH compliant No content of PFCs or 'PFAS' Californian Proposition 65 list compliant LBC Red list compliant Healthier Hospitals compliant

Green building certificates

Greengard Gold: Low chemical emission Health Product Declaration (HPD): Declaring textile content and substance

Country of origin The Netherlands

Launch

2024

Warranty

5 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information kvadrat.dk

kvadrat febrik