

#### Rumor

Design: Bertjan Pot

Type: Upholstery

Composition: 21% new wool, 12% recycled polyester,

7% nylon, 60% recycled polyester filling

Yarn type: Worsted

Binding: Knit

Width: approx. 165 cm, 65 inches Weight: approx. 1280 g/lin.m, 41 oz/ly

Repeat: None

Colour difference may occur

Foreign fibers may occur in light colours

Cleaning: Vacuuming gently. Washable at 30°C if loose covers.

Drip drying.

Shrinkage approx. 3% Mount in moist condition

More info: Care and maintenance kvadrat.dk

₩ X 🛛 🗷 P







## Rumor

#### **Abrasion**

Approx. 100.000 Martindale rubs, EN ISO 12947

Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention

#### **Pilling**

Note 4-5, EN ISO 12945

#### Lightfastness

Note 6-7, ISO 105-B02

#### Fastness to rubbing

Dry note 4-5, ISO 105-X12 Wet note 4, ISO 105-X12

### Absorption

150 mm airgap 0.70/Class C (flat), EN ISO 354 100 mm airgap

0.60/Class C (flat), EN ISO 354

#### Airflow

360 Pa s/m EN 29035

#### Flame resistance

AS/NZS 3837 class 1 ASTM E84 Class A Unadhered BS 5852 part 1 ignition source 0 BS 5852 Crib 5, with treatment \* EN 1021-1/2 IMO FTP Code 2010 part 8 UNI 9175 1IM US Cal. Bull. 117-2013

Free from added flame-retardant chemicals as standard

\* To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants

#### **ACT Guidelines Knit fabrics**

## Flammability

US Cal. Bull. 117-2013

### **Dry & Wet Crocking AATCC 8**

Dry Crocking: Grade 5.0 Wet Crocking: Grade 4.0

## Colour Fastness to Light AATCC 16

Grade 4.5 minimum 40 hours

## **Physical properties**

Pilling Class 4-5 ASTM D4970 Breaking Strength warp 127 / weft 219 lbs, ASTM D5034 Seam Slippage warp 144 / weft 156 lbs, ASTM D4034

#### **Abrasion**

100.000 cycles Martindale - High Traffic / Public Space

#### **Quality benefits**

Great wear- and stretchability Very good abrasion Good lightfastness Flame retardant

#### **Environmental benefits**

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions
REACH compliant
No content of PFCs or 'PFAS'
Californian Proposition 65 list compliant
LBC Red list compliant
Healthier Hospitals compliant

### Green building certificates

Greengard Gold: Low chemical emission Health Product Declaration (HPD): Declaring textile content and substance

## Country of origin

The Netherlands

#### Launch

2024

#### Warranty

5 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information kvadrat.dk

# kvadrat febrik