

Journey

Design: Kinnasand

Type: Curtain

Composition: 100% Trevira CS

Yarn type: Staple Binding: Twill

Width: Approx. 290 cm, 114 inches Weight: Approx. 800 g/lin.m, 25.8 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Washing at max. 60°C.

Drip drying.

Shrinkage approx. 1% / 0% when washed at 60 °C. Ironing might be necessary. Iron on the reverse side

Disinfection, see www.kvadrat.dk

More info: Care and maintenance kvadrat.dk

 $\underline{\omega} \times \underline{\otimes} \overline{a} \underline{a} \underline{p}$







Journey

Lightfastness

Note 4-7 ISO 105-B02

Absorption

100 mm airgap

0.50/Class D (flat), 0.70/Class C (waved) EN ISO 354

Airflow

1245 Pa s/m EN 29053

Flame resistance

ASTM E84 Class A Unadhered BS 5867 part 2 type C CAN ULC S102 CAN ULC S109 DIN 4102 B1 EN 13501-1, B-s1, d0

EN 13 773 class 1 GB 8624 B1

IMO FTP Code 2010 Part 5

NF P 92 507 M1 NFPA 701

ACT Guidelines Woven fabrics

Flammability

NFPA 701

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 4.5 Wet Crocking: Grade 5.0

Colour Fastness to Light AATCC 16

Grade 5.0 minimum 60 hours

Physical properties

Seam Slippage warp 196 / weft 222 lbs. ASTM D434

Quality benefits

Permanent flame retardant Washable Acoustic performance



Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

No use of halogen-based flame retardants (incl. brominated and chlorinated)

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Mono material designed for circularity

Recyclable

Green Building certificates

Greenguard Gold: Low chemical emission Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Turkey

Warranty

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information kvadrat.dk

