

Trace

Design: Kinnasand

Type: Curtain

Composition: 100% polyester FR

Yarn type: Filament Binding: Plain

Width: Approx. 305 cm, 120 inches Weight: Approx. 150 g/lin.m, 4.8 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Washing at max. 60°C.

Drip drying.

Shrinkage approx. 2% / 0% when washed at 60°C.

Ironing might be necessary
Disinfection, see www.kvadrat.dk

More info: Care and maintenance kvadrat.dk

 $\underline{\omega} \times \underline{\otimes} \underline{a} \underline{p}$







Trace

Lightfastness

Note 6-7 ISO 105-B02

Airflow

<10 Pa s/m EN 29053

Flame resistance

BS 5867 part 2 type B CAN ULC S102 CAN ULC S109 DIN 4102 B1 IMO FTP Code 2010 Part 5 JIS L 1091 A-1 D NF P 92 507 M1 NFPA 701

ACT Guidelines Woven fabrics

Flammability

NFPA 701

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 5.0 Wet Crocking: Grade 5.0

Colour Fastness to Light AATCC 16

Grade 5.0 minimum 60 hours

Physical properties

Seam Slippage warp 32 / weft 45 lbs. ASTM D434 Not required fabric under weight

Quality benefits

Very good lightfastness Permanent flame retardant Washable

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

No use of halogen-based flame retardants (incl. brominated and chlorinated)

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Mono-material designed for circularity

Recyclable



Green Building certificates

Greenguard Gold: Low chemical emission Health Product Declaration (HPD): Declaring textile content and substance

Special recommendations

Do not tear - only cut

Country of origin

Italy

Warranty

10 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information kvadrat.dk

