



Skydo II

Design: Kinnasand

Type: Curtain

Composition: 100% polyester FR

Yarn type: Filament

Binding: Dobby

Width: Approx. 290 cm, 114 inches

Weight: Approx. 550 g/lin.m, 17.7 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Washing at max. 30°C.

Drip drying.

Shrinkage approx. 1% / 0% when washed at 30°C.

Ironing might be necessary

Disinfection, see www.kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year warranty



Skydo II

Lightfastness

Note 3-7 ISO 105-B02

Absorption

150 mm airgap

0.35/Class D (flat) EN ISO 354

100 mm airgap

0.35/Class D (flat), 0.60/Class C (waved) EN ISO 354

EN ISO 354

Flame resistance

ASTM E84 Class A unadhered

BS 5867 part 2 type B

CAN ULC S102

CAN ULC S109

DIN 4102 B1

EN 13 773 class 1

IMO FTP Code 2010 Part 5

IMO FTP Code 2010 Part 7

NFPA 701

ACT Guidelines Woven fabrics

Flammability

NFPA 701

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 5.0

Wet Crocking: Grade 5.0

Colour Fastness to Light AATCC 16

Grade 5.0 minimum 60 hours

Physical properties

Seam Slippage warp 33.5 / weft 19 lbs. ASTM D434

Seam Slippage ASTM D434

Quality benefits

Dim Out

Acoustic performance

Permanent flame retardant

Washable

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

No use of halogen-based flame retardants (incl. brominated and chlorinated)

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Mono-material designed for circularity

Recyclable

Green Building certificates

Greenguard Gold: Low chemical emission
Health Product Declaration (HPD): Declaring textile content
and substance

Country of origin

Japan

Warranty

10 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard
material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information
kvadrat.dk