



Autumn

Design: Teruhiro Yanagihara

Type: Upholstery

Composition: 100% recycled polyester

Yarn type: Filament

Binding: Dobby

Width: Approx. 140 cm, 55 inches

Weight: Approx. 590 g/lin.m, 19 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week if fixed covers. Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water based glue. Pay attention to temperature and amount of cleaning fluid.

Also washable at 60°C, half wash load. Drip drying.

Mount in moist condition. Shrinkage app. 4/1% at 60°C.

Be aware of increased shrinking and creasing the higher the temperature.

Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year
warranty



Autumn

Abrasion

Min. 50.000 Martindale rubs, EN ISO 12947

Pilling

Note 4, EN ISO 12945

Seam slippage

Seam parallel to warp: 4.0 mm parallel to weft: 4.0 m
EN ISO 13 936-2 180 Newton

Snagging

Grade 1, ICI Testmethod FAB 29, Tumble-Box

Lightfastness

Note 6-7 ISO 105-B02

Fastness to rubbing

Dry note 4-5 ISO 105-X12

Wet note 4-5 ISO 105-X12

Flame resistance

AS/NZS 3837 class 1

ASTM E84 Class A Unadhered

ASTM E84 Class A Adhered

BS 5852 Part 1 with treatment *

BS 5852 Crib 5 with treatment *

EN 1021-1/2

IMO FTP Code 2010 : Part 8

SN 198 898 5.2 with treatment *

US Cal. Bull. 117-2013

Free from added flame retardant chemicals as standard

** To pass this test flame retardant treatment is necessary.*

We are looking into more environmentally friendly alternatives but for now the external finisher may use a treatment containing halogen based flame retardants

ACT Guidelines Woven fabrics**Flammability**

US Cal. Bull. 117-2013

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 4.5-5.0

Wet Crocking: Grade 4.5-5.0

Colour Fastness to Light AATCC 16

Grade 4.0-5.0 minimum 40 hours

Physical properties

Pilling Class 4 ASTM D4970

Breaking Strength warp 306 / weft 217 lbs. ASTM D5034

Seam Slippage warp 120 / weft 108.5 lbs. ASTM D 4034

Abrasion ASTM D4966

50.000 cycles Martindale – High Traffic / Public Spaces

Quality benefits

Complies with Möbelfakta

Good abrasion

Very good lightfastness

Washable

Environmental benefits

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Healthier Hospitals compliant

No content of PFCs or 'PFAS'

Mono-material designed for circularity

Recyclable

Green building certificates

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Turkey

Launch

2024

Warranty

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information

kvadrat.dk