


## Azure Outdoor

Type: Outdoor upholstery, upholstery  
Composition: 90% recycled polyester, 10% polyester  
PFAS-free water repellent finish  
Yarn type: Filament  
Binding: Dobby  
Width: Approx. 140 cm, 55 inches  
Weight: Approx. 510 g/lin.m, 16 oz/ly

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week  
Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary.  
Washable at 30 °C if loose covers. Drip drying.  
Shrinkage app. 2 %  
Mount in moist condition.  
Mildew growth is not promoted by the textile, but mildew may grow on dirt and other foreign substances if not removed.  
Keep the textile dry to avoid mildew and spores to stick.  
Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year warranty



## Azure Outdoor

### Abrasion

Approx. 45.000 Martindale rubs, EN ISO 12947

### Pilling

Note 5, EN ISO 12945

### Seam slippage

Seam parallel to warp: 3.5 mm parallel to weft: 2.5 mm  
EN ISO 13 936-2 180 Newton

### Colour fastness to light

Note 6-7 ISO 105-B02

### Colour fastness to weathering

Note 7-8 ISO 105-B04  
Colour 984 5-6

### Colour fastness to chlorine water

Note 4-5 ISO 105-E03

### Colour fastness to sea water

Note 4-5 ISO 105-E02

### Fastness to rubbing

Dry note 4-5 ISO 105-X12  
Wet note 4-5 ISO 105-X12

### Spray test (water)

Note 5 EN 4920

### Soil repellent

Note min. 4 depending on colour

### Flame resistance

AS/NZS 3837 class 1  
ASTM E84 Class A Adhered  
ASTM E84 Class A Unadhered  
BS 5852 Crib 5 with treatment \*  
BS 5852 Part 1 with treatment\*  
EN 1021-1/2  
SN 198 898 5.2 with treatment \*  
US Cal. Bull. 117-2013

\* To pass this test flame retardant treatment is necessary.  
We are looking into more environmental friendly alternatives  
but for now the external finisher may use a treatment  
containing halogen based flame retardants

## **ACT Guidelines Woven fabrics**

### **Flammability**

US Cal. Bull. 117-2013

### **Dry & Wet Crocking AATCC 8**

Dry Crocking: Grade 4.0-5.0

Wet Crocking: Grade 4.0-5.0

### **Colour Fastness to Light AATCC 16**

Grade 4.5-5.0 minimum 40 hours

### **Physical properties**

Pilling Class 5 ASTM D4970

Breaking Strength warp 300 / weft 310 lbs. ASTM D5034

Seam Slippage warp 106.5 / weft 124 lbs. ASTM D 4034

### **Abrasion ASTM D4966**

45.000 cycles Martindale – High Traffic / Public Spaces

### **Quality benefits**

Suitable for outdoor use

Resistance to chlorine and seawater

Resistance to weathering and mildew

Very good lightfastness

Flame retardant

Washable

### **Environmental benefits**

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

No use of halogen-based flame retardants (incl. brominated and chlorinated)

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Healthier Hospitals compliant

No content of PFCs or 'PFAS'

Mono-material designed for circularity

Recyclable

### **Green building certificates**

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content and substance

### **Country of origin**

Holland

### **Launch**

2024

### **Warranty**

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information

kvadrat.dk