



Highlight

Design: Kinnasand

Type: Curtain

Composition: 100% polyester FR

Yarn type: Filament

Binding: Dobby

Width: Approx. 147 cm, 58 inches

Weight: Approx. 640 g/lin.m, 20.6 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Washing at max. 60°C.

Drip drying.

Shrinkage approx. 1% / 0% when washed at 60°C.

Ironing might be necessary

Disinfection, see www.kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year warranty



Highlight

Lightfastness

Note 4-7 ISO 105-B02

Light Transmission DIN EN 410

<1% (test is performed in flat state)

Absorption EN ISO 354

100 mm airgap

0.55/Class D (flat), 0.90/Class A (waved)

150 mm airgap

0.60/Class C (flat), 0.90/Class A (waved)

Airflow

2073 Pa s/m EN 29053

Flame resistance

BS 5867 part 2 type B

CAN ULC S102

DIN 4102 B1

EN 13 773 class 1

IMO FTP Code 2010 Part 5

JIS L 1091 A-1 D

NF P 92 507 M1

NFPA 701

ACT Guidelines Woven fabrics

Flammability

NFPA 701

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 5.0

Wet Crocking: Grade 5.0

Colour Fastness to Light AATCC 16

Grade 5.0 minimum 60 hours

Physical properties

Seam Slippage warp 22 / weft 28 lbs. ASTM D434

Seam Slippage ASTM D434

Quality benefits

Dim out

Permanent flame retardant

Washable

Acoustic performance

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions
No use of halogen-based flame retardants (incl. brominated and chlorinated)
REACH compliant
Californian Proposition 65 list compliant
LBC Red list compliant
Mono material designed for circularity
Recyclable

Green Building certificates

Greenguard Gold: Low chemical emission
Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Japan

Warranty

10 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information
kvadrat.dk