Test Report

Report No.: A 884227-3



DANISH **TECHNOLOGICAL** INSTITUTE

Gregersensvej DK-2630 Taastrup Tel. +45 72 20 20 00 Fax +45 72 20 20 19

info@teknologisk.dk www.teknologisk.dk

Page 1 of 1 Chf/leln Order no.: 884227 No. of appendices: 1

Assignor:

Kinnasand GmbH Danziger Strasse 6 26655 Westerstede

Germany

Attn.: Sonja Fröhlich

Subject:

Curtain fabric Art. Site 6882 (as per info from the assigner).

Sampling:

The test material was sampled by the client and received at the Danish Technological In-

stitute 15.08.2019

Method:

See Appendix 1.

Period:

The testing was completed 09.09.2019

Result:

Individual results appear from Appendix 1.

Storage:

The test material will be destroyed after 6 months, unless otherwise agreed.

Terms:

The accredited test was carried out according to DANAK's general conditions see www.danak.dk and according to the General Terms and Conditions regarding Commissioned Work Accepted by the Danish Technological Institute, which apply at the time of signing the agreement. The test is only valid for the tested specimen. The test report

may only be extracted, if the laboratory has approved the extract.

Date/place:

11.09.2019, Danish Technological Institute, Wood and Biomaterials, Textile, Taastrup

Charlotte Fischer 196 Direct 145 72 20 21 35 Firmul charlotte fischer@teknologisk dk

Charlotte Fischer

Signature:

Test responsible

Co-signatory





Report no.:

A 884227-3

Appendix:

1 1 of 2

Page: Initials:

Chf/leIn

Test Methods	Results	
Colour fastness to artificial light	0001	
DS/EN ISO 105:B02:2014	Colour fastness:	7
Method 2		
1-8 scale, 8 best rating		
Normal conditions		
Apparatus: Atlas Ci4000 Xenon		
Weather-Ometer		
Colour fastness to artificial light	0002	
DS/EN ISO 105:B02:2014	Colour fastness:	7
Method 2		
1-8 scale, 8 best rating Normal conditions		
Apparatus: Atlas Ci4000 Xenon		
Weather-Ometer		
Colour fastness to artificial light	0003	
DS/EN ISO 105:B02:2014	Colour fastness:	7
Method 2	Coloui lastiless.	,
1-8 scale, 8 best rating		
Normal conditions		
Apparatus: Atlas Ci4000 Xenon		
Weather-Ometer		
Colour fastness to artificial light	0004	
DS/EN ISO 105:B02:2014	Colour fastness:	6
Method 2		
1-8 scale, 8 best rating		
Normal conditions		
Apparatus: Atlas Ci4000 Xenon		
Weather-Ometer		
Colour fastness to artificial light	0005	c 7
DS/EN ISO 105:B02:2014 Method 2	Colour fastness:	6-7
1-8 scale, 8 best rating		
Normal conditions		
Apparatus: Atlas Ci4000 Xenon		
Weather-Ometer		
Colour fastness to artificial light	0006	
DS/EN ISO 105:B02:2014	Colour fastness:	6
Method 2		
1-8 scale, 8 best rating		
Normal conditions		
Apparatus: Atlas Ci4000 Xenon		
Weather-Ometer		
Colour fastness to artificial light	0007	
DS/EN ISO 105:B02:2014 Method 2	Colour fastness:	6-7
1-8 scale, 8 best rating		
Normal conditions		
Apparatus: Atlas Ci4000 Xenon		
Weather-Ometer		
Colour fastness to artificial light	0012	
DS/EN ISO 105:B02:2014	Colour fastness:	6-7
Method 2		
1-8 scale, 8 best rating		
Normal conditions		
Apparatus: Atlas Ci4000 Xenon		
Weather-Ometer		

DANISH TECHNOLOGICAL INSTITUTE

Report no.: Appendix:

A 884227-3

Page: Initials: 2 of 2 Chf/leln

Test Methods	Results	
Colour fastness to artificial light DS/EN ISO 105:B02:2014 Method 2 1-8 scale, 8 best rating Normal conditions Apparatus: Atlas Ci4000 Xenon Weather-Ometer	0013 Colour fastness:	6
Colour fastness to artificial light DS/EN ISO 105:B02:2014 Method 2 1-8 scale, 8 best rating Normal conditions Apparatus: Atlas Ci4000 Xenon Weather-Ometer	0014 Colour fastness:	6
Colour fastness to artificial light DS/EN ISO 105:B02:2014 Method 2 1-8 scale, 8 best rating Normal conditions Apparatus: Atlas Ci4000 Xenon Weather-Ometer	0021 Colour fastness:	6-7
Colour fastness to artificial light DS/EN ISO 105:B02:2014 Method 2 1-8 scale, 8 best rating Normal conditions Apparatus: Atlas Ci4000 Xenon Weather-Ometer	0025 Colour fastness:	6-7
Colour fastness to artificial light DS/EN ISO 105:B02:2014 Method 2 1-8 scale, 8 best rating Normal conditions Apparatus: Atlas Ci4000 Xenon Weather-Ometer	0033 Colour fastness:	6-7