


## Hero Heather

Type: Upholstery, panel fabric  
Composition: 97% new wool, 3% recycled nylon  
Yarn type: Worsted / woollen  
Binding: Devon weave  
Width: Approx. 140 cm, 55 inches  
Weight: Approx. 560 g/lin.m, 18 oz/ly  
Repeat: None

Colour difference will occur

Cleaning: Vacuum clean frequently, ideally every week. Remove stains as soon as they occur, with clean warm water or sparkling water. Please be aware that stain removal will cause a darker area as the wool fibers rise when exposed to water. This can only be reduced by gentle atomizing water over the entire furniture. Extraction clean when necessary. Avoid using steam.

More info: Care and maintenance kvadrat.dk



10 year warranty



# Hero Heather

## Abrasion

Approx. 45.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.*

## Pilling

Note 3-4, EN ISO 12945

## Seam slippage

Seam parallel to warp: 2.0 mm parallel to weft: 2.5 mm  
EN ISO 13 936-2 180 Newton

## Lightfastness

Note 6 ISO 105-B02

## Fastness to rubbing

Dry note 4-5 ISO 105-X12  
Wet note 4-5 ISO 105-X12

## Absorption

150 mm airgap  
0.65/Class C (flat), 0.90/Class A (waved) EN ISO 354  
100 mm airgap  
0.55/Class D (flat), 0.80/Class B (waved) EN ISO 354

## Airflow

348 Pa s/m EN 29053

## Flame resistance

AS/NZS 1530.3  
AS/NZS 3837 class 1  
ASTM E84 Class A Adhered  
ASTM E84 Class A Unadhered  
BS 5852 crib 5 with treatment \*  
BS 5852 part 1  
BS 7176 Low Hazard  
EN 1021-1/2  
EN 13 773 class 1 with treatment \*  
IMO FTP Code 2010 Part 8  
NF D 60 013  
NFPA 701 with treatment \*  
SN 198 898 5.3 with treatment \*  
UNI 9175 1IM  
US Cal. Bull. 117-2013  
ÖNORM B1/Q1

Free from added flame-retardant chemicals as standard.

*\* To pass this test flame retardant treatment is necessary. We are looking into more environmental friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants.*

## **ACT Guidelines Woven fabrics**

### **Flammability**

US Cal. Bull. 117-2013

### **Dry & Wet Crocking AATCC 8**

Dry Crocking: Grade 4.0-5.0

Wet Crocking: Grade 3.5-5.0

### **Colour Fastness to Light AATCC 16**

Grade 4.0-5.0 minimum 40 hours

### **Physical properties**

Breaking Strength warp 140 / weft 88 lbs, ASTM D5034

Seam Slippage warp 155 / weft 99.5 lbs, ASTM D4034

### **Abrasion ASTM D4966**

45.000 cycles Martindale – High Traffic / Public Spaces

### **Quality benefits**

Complies with Möbelfakta

Good abrasion

Very good lightfastness

Flame retardant

Acoustic performance

### **Benefits of wool**

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb/  
give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

## **Environmental benefits**

EU Ecolabel compliant

Free of intentionally added PFAS

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Healthier Hospitals compliant

No content of PFCs or 'PFAS'

## **Green building certificates**

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content  
and substance

## **Special recommendations**

Iron without steam

## **Country of origin**

United Kingdom

## **Launch**

2023

## **Warranty**

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard  
material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information

kvadrat.dk