

Confidential Report

Our Ref: 23/62052A/05/24





BTTG		Date:	16 May 2024
TESTING • CERTIFICATION • AUDITING		Our Ref: Your Ref:	23/62052A/05/24
		Page:	1 of 4
Client:	Kvadrat High Performance Textiles		
	Kiefte 18 7151 HZ Eibergen Netherlands		
Job Title:	Fire Test on One Material Sample		
Clients Order Ref:			
Date of Receipt:	07 May 2024		
Date Test Started:	16 May 2024		
Description of Sample:	One sample of material, which was referenced	by the client as;	
	Unlit Block Out/KHPT Fabric 190 (black)		
Work Requested:	We were asked to make the following fire test:		
	BS 5867: Part 2:Type B:2008 (2015)		

subcontracted test, UKAS accredited

** subcontracted test, EN ISO/IEC 17025 accredited

*** not UKAS accredited

Note: This report relates only to the items tested.

Shirley® Technologies Limited. Registered Office: Wira House, West Park Ring Road, Leeds, LS16 6QL. A company registered in England & Wales with company number 04669651. VAT Number GB 816764800. BTTG[™] and Shirley® are trade names of Shirley Technologies Ltd. The supply of all goods and services is subject to our standard terms of business, copies of which are available on request. Our laboratories are accredited to EN ISO/IEC 17025.





16 May 2024	Date:
23/62052A/05/24 	Our Ref: Your Ref:
2 of 4	Page:

Client:

Kvadrat High Performance Textiles

BS 5867: Part 2: 2008 (2015): Type B Curtains, Drapes and Blinds

Pre-treatment

The sample was not subjected to any water soaking procedure.


Conditioning

The test specimens were conditioned for at least 24 hours in the standard atmosphere of 65 ± 5 % relative humidity (R.H.) and 20 ± 2 °C.

Testing

Three specimens from both length and width were tested in accordance with BS EN ISO 15025: Procedure A (surface ignition):2002.

Each specimen was subjected to an applied flame using propane and a 15 second flame application time. The results obtained (shown in the table below) were assessed according to the requirements of BS 5867: Part 2:Type B:2008 (2015).







16 May 2024	Date:
23/62052A/05/24 	Our Ref: Your Ref:
3 of 4	Page:

Client:

Kvadrat High Performance Textiles

Results - Testing as received.

	Length			Width		
Specimen No.	1	2	3	4	5	6
Flame reached an edge	No	No	No	No	No	No
Hole reached an edge	No	No	No	No	No	No
Flaming debris separated	No	No	No	No	No	No
Afterflame (s)	0	0	0	0	0	0
Afterglow (s)	6	0	2	13	5	8

Requirements - Any "Yes" means fail except if only one specimen fails a further 6 specimens are tested, it the second 6 specimens all pass the result is a pass.

Result: Pass

Comment

The fabric meets the Type B performance requirements of BS 5867: Part 2: 2008 – the fabric must be clearly labelled `If wetted in any way it is essential to re-treat the fabric to meet flammability requirements`.

The material should be identified with the manufacturers name, trademark or other identifying mark, the statement `Flammability complies with the requirements of BS 5867: Part 2, Type B and instructions of any special precautions to be taken concerning care (including cleansing) of the curtain, drape or window blind to be manufactured from the fabric, preferably using an appropriate care labelling symbol in accordance with BS EN 23758 and taking account of the pre-treatment used in this test and the requirements of Clause 4 of BS 5867: Part 2: 2008 (2011). If the fabric is unsuitable for cleansing, this shall be stated.

Where required to make a judgement to any pass/fail criteria an estimation of uncertainty of measurement has been taken into account. Under our Policy we have used a non-binary decision rule.

See our decision rules Policy (<u>https://www.bttg.co.uk/about-us/decision-rules-policy/</u>) for further information.





16 May 2024	Date:
23/62052A/05/24 	Our Ref: Your Ref:
4 of 4	Page:

Client:

Kvadrat High Performance Textiles

Uncertainty Budget

Type B $-\pm$ 1 seconds for after flame time and afterglow time.

For the remaining criteria, measurements are not taken and pass/fail is related to flame extremities and flaming debris, as such any risk of false acceptance/false rejection is inherent with this standard and would be outside of 95% probability in any case. As such UoM is Zero providing all input parameters are correct.

Reported by:....

..... R Greasley, Laboratory Technician

...... B Bland, Technical Customer Service Officer

Countersigned by:....

Enquiries concerning this report should be addressed to Customer Services.





Copyright © 2024 Shirley Technologies Limited. All rights reserved.



Confidential Report

Our Ref: 23/62052B/05/24





BTTG		Date:	16 May 2024
TESTING • CERTIFICATION • AUDITING		Our Ref: Your Ref:	23/62052B/05/24
		Page:	1 of 4
Client:	Kvadrat High Performance Textiles		
	Kiefte 18 7151 HZ Eibergen Netherlands		
Job Title:	Fire Test on One Material Sample		
Clients Order Ref:			
Date of Receipt:	07 May 2024		
Date Test Started:	16 May 2024		
Description of Sample:	One sample of material, which was referenced	by the client as;	
	Unlit Block Out/KHPT Fabric 100 (white)		
Work Requested:	We were asked to make the following fire test:		
	BS 5867: Part 2:Type B:2008 (2015)		

subcontracted test, UKAS accredited

** subcontracted test, EN ISO/IEC 17025 accredited

*** not UKAS accredited

Note: This report relates only to the items tested.

Shirley® Technologies Limited. Registered Office: Wira House, West Park Ring Road, Leeds, LS16 6QL. A company registered in England & Wales with company number 04669651. VAT Number GB 816764800. BTTG[™] and Shirley® are trade names of Shirley Technologies Ltd. The supply of all goods and services is subject to our standard terms of business, copies of which are available on request. Our laboratories are accredited to EN ISO/IEC 17025.





16 May 2024	Date:
23/62052B/05/24 	Our Ref: Your Ref:
2 of 4	Page:

Client:

Kvadrat High Performance Textiles

BS 5867: Part 2: 2008 (2015): Type B Curtains, Drapes and Blinds

Pre-treatment

The sample was not subjected to any water soaking procedure.


Conditioning

The test specimens were conditioned for at least 24 hours in the standard atmosphere of 65 ± 5 % relative humidity (R.H.) and 20 ± 2 °C.

Testing

Three specimens from both length and width were tested in accordance with BS EN ISO 15025: Procedure A (surface ignition):2002.

Each specimen was subjected to an applied flame using propane and a 15 second flame application time. The results obtained (shown in the table below) were assessed according to the requirements of BS 5867: Part 2:Type B:2008 (2015).







16 May 2024	Date:
23/62052B/05/24 	Our Ref: Your Ref:
3 of 4	Page:

Client:

Kvadrat High Performance Textiles

Results - Testing as received.

	Length			Width		
Specimen No.	1	2	3	4	5	6
Flame reached an edge	No	No	No	No	No	No
Hole reached an edge	No	No	No	No	No	No
Flaming debris separated	No	No	No	No	No	No
Afterflame (s)	0	0	0	0	0	0
Afterglow (s)	10	8	0	9	4	12

Requirements - Any "Yes" means fail except if only one specimen fails a further 6 specimens are tested, it the second 6 specimens all pass the result is a pass.

Result: Pass

Comment

The fabric meets the Type B performance requirements of BS 5867: Part 2: 2008 – the fabric must be clearly labelled `If wetted in any way it is essential to re-treat the fabric to meet flammability requirements`.

The material should be identified with the manufacturers name, trademark or other identifying mark, the statement `Flammability complies with the requirements of BS 5867: Part 2, Type B and instructions of any special precautions to be taken concerning care (including cleansing) of the curtain, drape or window blind to be manufactured from the fabric, preferably using an appropriate care labelling symbol in accordance with BS EN 23758 and taking account of the pre-treatment used in this test and the requirements of Clause 4 of BS 5867: Part 2: 2008 (2011). If the fabric is unsuitable for cleansing, this shall be stated.

Where required to make a judgement to any pass/fail criteria an estimation of uncertainty of measurement has been taken into account. Under our Policy we have used a non-binary decision rule.

See our decision rules Policy (<u>https://www.bttg.co.uk/about-us/decision-rules-policy/</u>) for further information.





16 May 2024	Date:
23/62052B/05/24 	Our Ref: Your Ref:
4 of 4	Page:

Client:

Kvadrat High Performance Textiles

Uncertainty Budget

Type B $-\pm$ 1 seconds for after flame time and afterglow time.

For the remaining criteria, measurements are not taken and pass/fail is related to flame extremities and flaming debris, as such any risk of false acceptance/false rejection is inherent with this standard and would be outside of 95% probability in any case. As such UoM is Zero providing all input parameters are correct.

Reported by:.....

..... R Greasley, Laboratory Technician

...... B Bland, Technical Customer Service Officer

Countersigned by:....

Enquiries concerning this report should be addressed to Customer Services.

