

Zone

Design: Kinnasand

Type: Curtain

Composition: 65% recycled polyester FR 30% polyester FR

5% polyester Yarn type: Filament Binding: Dobby

Width: Approx. 325 cm, 128 inches Weight: Approx. 205 g/lin.m, 6.6 oz/ly

Repeat: Approx. 150 cm, 59 inches V, 0 cm, 0 inches H

Colour difference may occur

Cleaning: Washing at max. 60°C.

Drip drying.

Shrinkage approx. 1% / 0% when washed at 60°C.

Ironing might be necessary
Disinfection, see www.kvadrat.dk

More info: Care and maintenance kvadrat.dk

₩ X 🛛 🗷 🕑







Zone

Lightfastness

Note 4-6 ISO 105-B02

Airflow

<10 Pa s/m EN 29053

Flame resistance

BS 5867 Part 2 type B DIN 4102 B1 NFPA 701

ACT Guidelines Woven fabrics

Flammability

NFPA 701

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 5.0 Wet Crocking: Grade 4.5

Colour Fastness to Light AATCC 16

Grade 4.0 minimum 60 hours

Physical properties

Seam Slippage ASTM D434 Not required fabric under weight

Quality benefits

Permanent flame retardant Washable

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions REACH compliant Californian Proposition 65 list compliant LBC Red list compliant

Green Building certificates

Greenguard Gold: Low chemical emission Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Italy

Warranty

10 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information kvadrat.dk

