



Twilight

Lightfastness

Note 6-8 ISO 105-B02

Light Reflection DIN EN 410

8-48% (test is performed in flat state)

Light Transmission DIN EN 410

0-0.8% (test is performed in flat state)

Absorption

100 mm airgap

0.55/Class D (flat), 0.80/Class B (waved) EN ISO 354

Airflow

1374 Pa s/m EN 29053

Flame resistance

AS/NZS 1530.3

ASTM E84 Class A Adhered

ASTM E84 Class A Unadhered

BS 5867 part 2 type B

DIN 4102 B1

EN 13 773 class 1

EN 13501 B-s1, d0

IMO FTP Code 2010 Part 7

JIS L 1091 A-1 D

NF P 92 507 M1

NFPA 701

SN 198 898 5.1

UNI 9177 Classe 1

ACT Guidelines Woven fabrics

Flammability

NFPA 701

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 4.5

Wet Crocking: Grade 4.5

Colour Fastness to Light AATCC 16

Grade 4.5 minimum 60 hours

Physical properties

Seam Slippage warp 25 / weft 25.5 lbs. ASTM D434

Twilight

Design: Patricia Urquiola

Type: Dim-out curtain

Composition: 59% polyester FR, 41% polyester

Yarn type: Filament

Binding: Satin

Width: Approx. 300 cm, 118 inches

Weight: Approx. 1080 g/lin.m, 34.8 oz/ly

Repeat: none

Colour difference may occur

Cleaning: Washing at max. 60°C.

Drip drying.

Shrinkage approx. 1% / 1% when washed at 60°C.

Ironing might be necessary.

Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year
warranty



Quality benefits

+ 99% dim-out
Good lightfastness
Permanent flame retardant
Washable
Acoustic performance

Environmental benefits

Complies with EU Ecolabel
REACH compliant
Californian Proposition 65 list compliant
LBC Red list compliant
Healthier Hospitals compliant

Green Building certificates

Greenguard Gold: Low chemical emission
Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Turkey

Launch

2015

Warranty

10 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information
kvadrat.dk