



Mylla

Design: Note Design Studio

Type: Upholstery
Composition: 100% recycled polyester
Yarn type: Filament
Binding: Knit
Width: approx. 134 cm, 53 inches
Weight: approx. 860 g/lin.m, 27.7 oz/ly
Repeat: None

Colour difference may occur

Cleaning: Vacuuming gently.
Washable at 60°C if loose covers.
Drip drying.
Shrinkage approx. 1%
Mount in moist condition

More info: Care and maintenance kvadrat.dk



5 year
warranty



Mylla

Abrasion

Approx. 50.000 Martindale rubs, EN ISO 12947

Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention

Pilling

Note 5, EN ISO 12945

Lightfastness

Note 6-7, ISO 105-B02

Fastness to rubbing

Dry note 4-5, ISO 105-X12

Wet note 4-5, ISO 105-X12

Absorption

150 mm airgap

0.70/Class C (flat), EN ISO 354

100 mm airgap

0.60/Class C (flat), EN ISO 354

Airflow

432 Pa s/m EN 29035

Flame resistance

AS/NZS 3837 class 2

ASTM E84 Class A Unadhered

ASTM E84 Class A Adhered

BS 5852 part 1, with treatment*

BS 5852 Crib 5, with treatment*

EN 1021-1/2

US Cal. Bull. 117-2013

Free from added flame-retardant chemicals as standard

** To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants*

ACT Guidelines Knit fabrics

Flammability

US Cal. Bull. 117-2013

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 5.0

Wet Crocking: Grade 5.0

Colour Fastness to Light AATCC 16

Grade 4.0 minimum 40 hours

Physical properties

Pilling Class 4-5 ASTM D4970

Breaking Strength warp 118 / weft 484 lbs, ASTM D5034

Elongation warp 139 / weft 62 %, ASTM D5034-09

Seam Slippage warp 134 / weft 101 lbf, ASTM D4034

Tounge Tear warp 19/ weft 32 lbf, ASTM D2261-13

Bursting Strength 10 lbf, ASTM D 3787-16

Abrasion

50.000 cycles Martindale – High Traffic / Public Space

Quality benefits

Great wear- and stretchability

Very good abrasion

Good lightfastness

Flame retardant

Environmental benefits

Recycled content

Follow the EU Ecolabel dye restrictions incl. AZO dye

and heavy metal restrictions

No use of halogen-based flame retardants (incl. brominated and chlorinated)

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Free of intentionally added PFAS

Green building certificates

Greengard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

The Netherlands

Launch

2025

Warranty

5 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information

kvadrat.dk