



## Technicolour

Design: Peter Saville

Type: Upholstery, panel fabric

Composition: 100% new English wool

Yarn type: Worsted

Binding: Plain

Width: Approx. 140 cm, 55 inches

Weight: Approx. 430 g/lin.m, 14 oz/ly

Foreign fibers will occur in light colours

Due to the structure of the yarn's irregularities will occur

Colour difference will occur

Cleaning: Vacuum clean frequently, ideally every week.

Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary.

Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid.

Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year  
warranty



## Technicolour

### Abrasion

Approx. 80.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention*

### Pilling

Note 4, EN ISO 12945

### Seam slippage

Seam parallel to warp: 10.0 mm parallel to weft: 8.1 mm  
EN ISO 13 936-2 180 Newton

### Lightfastness

Note 6-7 ISO 105-B02

### Fastness to rubbing

Dry note 4-5 ISO 105-X12

Wet note 3-5 ISO 105-X12

### Airflow

301 Pa s/m EN 29053

### Flame resistance

AS/NZS 3837 class 2

ASTM E84 Class A Unadhered

ASTM E84 Class A Adhered

BS 5852 crib 5 with treatment \*

BS 5852 part 1 with treatment \*

BS 7176 Low Hazard

EN 1021-1/2

IMO FTP Code 2010 Part 8

NF D 60 013

SN 198 898 5.3 with treatment \*

UNI 9175 1IM

US Cal. Bull. 117-2013

Free from added flame retardant chemicals as standard

*\* To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants*

# kvadrat

## **ACT Guidelines Woven fabrics**

### **Flammability**

US Cal. Bull. 117-2013

### **Dry & Wet Crocking**

Dry Crocking: Grade 4.5-5.0

Wet Crocking: Grade 3.0-5.0

### **Colour Fastness to Light**

Grade 4.0-5.0 minimum 40 hours

### **Physical properties**

Pilling Class 4

Breaking Strength warp 133 / weft 131 lbs.

Seam Slippage warp 26 / weft 24 lbs.

### **Abrasion**

80.000 cycles Martindale – High Traffic / Public Spaces

### **Benefits of wool**

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb/  
give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

### **Quality benefits**

Complies with Möbelfakta

Very good abrasion

Very good lightfastness

Flame retardant

## **Environmental benefits**

EU Ecolabel compliant

Free of intentionally added PFAS

Mono-material designed for circularity

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Healthier Hospitals compliant

## **Green building certificates**

Greenguard Gold: Low chemical emission

Environmental Product Declaration (EPD): 3rd Party Verified.

ISO 14025 & EN 15804. Developed in accordance with the  
European standard EN 15804+A2.

Health Product Declaration (HPD): Declaring textile content  
and substance

## **Country of origin**

United Kingdom

## **Launch**

2025

## **Warranty**

10 years. See terms and conditions on [kvadrat.dk](https://kvadrat.dk)

Kvadrat packaging and cardboard is recyclable. Cardboard  
material is FSC certified and / or contains recycled content.

For further information

[kvadrat.dk](https://kvadrat.dk)