

# SAHCO

1831



## Tablu

Type: Upholstery

Composition: 67% new wool, 12% linen, 12% viscose,  
6% polyester, 3% nylon

Yarn type: Worsted

Binding: Jacquard

Width: Approx. 140 cm, 55 inches

Weight: Approx. 180 g/lin.m, 35 oz/ly

Repeat: Colour 142, 232, 332, 392, 572, 652:

Approx. 49 cm, 19.3 inches V, 84 cm, 33 inches H, 49 cm

Colour 152, 182, 482: Approx. 49 cm. 19.3 inches V,  
76 cm, 30 inches H

See last page for more details

Foreign fibers may occur in light colours

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week.

Remove stains as soon as they occur, with clean warm water  
or sparkling water. Extraction clean when  
necessary. Extraction cleaning might dissolve water based  
glue. Pay attention to temperature and amount of cleaning  
fluid.

Disinfection, see [www.kvadrat.dk/en/sahco](http://www.kvadrat.dk/en/sahco)



10<sup>year</sup>  
warranty



## Abrasion

Approx. 50.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance  
guidelines are not an indicator of product lifespan. Multiple  
factors affect fabric durability and appearance retention.*

## Pilling

Note 4 , EN ISO 12945

## Seam slippage

Seam parallel to warp: 2.5mm parallel to weft: 6.0 mm

EN ISO 13 936-2 180 Newton

## Snagging

Note 2 ICI Testmethod FAB 29, Tumble-Box

## Lightfastness

Note 6-7 ISO 105-Bo2

## Fastness to rubbing – to be confirmed

Dry note 4-5 ISO 105-X12

Wet note 3-5 ISO 105-X12

## Flame resistance

AS/NSZ 3837 class 2

BS 5852 Crib 5

BS 5852 Part 1

BS 7176 Low Hazard

EN 1021-1/2

IMO FTP Code 2020 : Part 8

ÖNORM B1 / Q1

UNI 9175 IIM

US Cal. Bull. 117-2013

Free from added flame-retardant chemicals as standard

## **ACT Guidelines Woven fabrics**

### **Flammability**

US Cal. Bull. 117-2013

### **Dry & Wet Crocking AATCC 8**

Dry Crocking: Grade 4.5-5.0

Wet Crocking: Grade 3.0-4.0

### **Colour Fastness to Light AATCC 16**

Grade 4.0-5.0 minimum 40 hours

### **Physical properties**

Pilling Class 4 ASTM D4970

Breaking Strength warp 181 / weft 262 lbs, ASTM D5034

Seam Slippage warp 28.5 / weft 133 lbs, ASTM D4034

### **Abrasion ASTM D4966**

50.000 cycles Martindale – High Traffic / Public Spaces

### **Quality benefits**

Complies with Möbelfakta -to be confirmed

Very good abrasion

Very good lightfastness

Flame retardant

### **Benefits of wool**

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb/  
give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

## **Environmental benefits**

Follow the EU Ecolabel dye restrictions incl. AZO dye  
and heavy metal restrictions

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Healthier Hospitals compliant

No content of PFCs or 'PFAS'

## **Green building certificates**

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile  
content and substance

## **Country of origin**

Norway

## **Launch**

2024

## **Warranty**

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard  
material is FSC certified and / or contains recycled  
content.

For further information

[kvadrat.dk/en/sahco](https://kvadrat.dk/en/sahco)

# SAHCO

1831

