



Guest

Design: Louise Sigvardt

Type: Upholstery, panel fabric
Composition: 100% recycled polyester
Yarn type: Chenille, filament
Binding: Jacquard
Width: Approx. 140 cm, 55 inches
Weight: Approx. 480 g/lin.m, 15 oz/ly
Repeat: None

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week if fixed covers. Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. No ironing, only steaming. Steaming might be necessary to remove pressure marks. Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid. Also washable at 60°C, half wash load. Drip drying. Mount in moist condition. Shrinkage app. 1% at 60°C.. Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk

160/

10 year
warranty



6575/25

Acoustic



Guest

Abrasion

App. 100.000 Martindale rubs, EN ISO 12947
Colour change: note 4-5 after 6000 rubs

Pilling

Note 4, EN ISO 12945

Seam slippage

Seam parallel to warp: 2.5 mm parallel to weft: 3.0 mm
EN ISO 13 936-2 180 Newton

Lightfastness

Note 5-7 ISO 105-B02

Fastness to rubbing

Dry note 4-5 ISO 105-X12
Wet note 4-5 ISO 105-X12

Absorption

150 mm airgap
0.70/Class C (flat), 0.85/Class B (waved) EN ISO 354
100 mm airgap
0.60/Class C (flat), 0.75/Class C (waved) EN ISO 354

Airflow

757 Pa s/m EN 29053

Flame resistance

AS/NZS 1530.3
AS/NZS 3837 class 2
ASTM E84 Class A Unadhered
ASTM E84 Class A Adhered
BS 5852 Part 1 with treatment *
BS 5852 Crib 5 with treatment *
BS 7176 Low Hazard
EN 1021-1/2
IMO FTP Code 2010 : Part 8
NFPA 701 with treatment *
SN 198 898 5.2 with treatment *
US Cal. Bull. 117-2013

Free from added flame retardant chemicals as standard

** To pass this test flame retardant treatment is necessary.
We are looking into more environmentally friendly
alternatives but for now the external finisher may use a
treatment containing halogen based flame retardants*

kvadrat

ACT Guidelines Woven fabrics

Flammability

US Cal. Bull. 117-2013

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 4.5-5.0

Wet Crocking: Grade 4.0-5.0

Colour Fastness to Light AATCC 16

Grade 4.0-5.0 minimum 40 hours

Physical properties

Pilling Class 4 ASTM D4970

Breaking Strength warp 347 / weft 96 lbs. ASTM D5034

Seam Slippage warp 98 / weft 107 lbs. ASTM D 4034

Abrasion ASTM D4966

100.000 cycles Martindale – High Traffic / Public Spaces

Quality benefits

Complies with Möbelfakta

Good abrasion

Very good lightfastness

Washable

Environmental benefits

Complies with EU Ecolabel

Recycled content

Free of intentionally added PFAS

Mono-material designed for circularity

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Healthier Hospitals compliant

Green building certificates

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Turkey

Launch

2024

Warranty

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information

kvadrat.dk

kvadrat