

SAHCO

1831



Saji

Type: Upholstery

Composition: 78% recycled polyester, 22% nylon

Yarn type: Filament

Binding: Jacquard

Width: Approx. 140 cm, 55 inches

Weight: Approx. 480 g/lin.m, 15.5 oz/ly

Repeat: Approx. 11 cm, 4.5 inches V / 16 cm, 6.5 inches H

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week.

Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary.

Extraction cleaning might dissolve water based glue. Pay attention to temperature and amount of cleaning fluid.

Washable at 30°C if loose covers. Drip drying.

Mount in moist condition.

Disinfection, see www.kvadrat.dk/en/sahco



10 year warranty



Abrasion

Approx. 45.000 Martindale rubs, EN ISO 12947

Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention

Pilling

Note 5, EN ISO 12945

Seam slippage

Seam parallel to warp: 3.0 mm, parallel to weft: 3.5 mm

EN ISO 13 936-2 180 Newton

Lightfastness

Note 5-6 ISO 105-B02

Fastness to rubbing

Dry note 4-5 ISO 105-X12

Wet note 4-5 ISO 105-X12

Flame resistance

BS 5852 Crib 5 with treatment *

BS 5852 part 1 with treatment *

EN 1021-1/2

NFPA 260

US Cal. Tech. Bull. 117

Free from added flame retardant chemicals as standard

** To pass this test flame retardant treatment is necessary.*

We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants

SAHCO

1831

ACT Guidelines Woven fabrics

Flammability

US Cal. Bull. 117-2013

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 5.0

Wet Crocking: Grade 4,5

Colour Fastness to Light AATCC 16

Grade 4-5 minimum 40 hours

Physical properties

Pilling ASTM D3511 Class 5

Breaking Strength ASTM D5034 warp 98 / weft 308 lbs

Seam Slippage ASTM D4034 warp 32.5 / weft 105 lbs

Abrasion ASTM D4966

45.000 cycles Martaindale – High Traffic

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Green building certificates

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Italy

Launch

2023

Warranty

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information

www.kvadrat.dk/en/sahco