

## Technicolour Fleck

### Abrasion

Approx. 100.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention*

### Pilling

Note 4, EN ISO 12945

### Seam slippage

Seam parallel to warp: 2.5 mm parallel to weft: 3.0 mm  
EN ISO 13 936-2 180 Newton

### Lightfastness

Note 4-7 ISO 105-B02

### Fastness to rubbing

Dry note 4-5 ISO 105-X12  
Wet note 4-5 ISO 105-X12

### Airflow

481 Pa s/m EN 29053

### Flame resistance

AS/NZS 3837 class 1  
ASTM E84 Class A Unadhered  
ASTM E84 Class A Adhered  
BS 5852 crib 5 with treatment \*  
BS 5852 part 1  
BS 7176 Low Hazard  
EN 1021-1/2  
IMO FTP Code 2010 Part 8  
NF D 60 013  
ÖNORM B1/Q1  
SN 198 898 5.3 with treatment \*  
UNI 9175 1IM  
US Cal. Bull. 117-2013

Free from added flame retardant chemicals as standard

*\* To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants*

### Technicolour Fleck

Design: Peter Saville

Type: Upholstery, panel fabric

Composition: 100% new English wool

Yarn type: Worsted

Binding: Plain

Width: Approx. 140 cm, 55 inches


Weight: Approx. 600 g/lin.m, 19.3 oz/ly

Due to the structure of the yarn's irregularities will occur  
Foreign fibers will occur  
Colour difference will occur

Cleaning: Vacuum clean frequently, ideally every week.  
Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid.

Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year warranty



# kvadrat

## **ACT Guidelines Woven fabrics**

### **Flammability**

US Cal. Bull. 117-2013

### **Dry & Wet Crocking**

Dry Crocking: Grade 4.5  
Wet Crocking: Grade 4.0

### **Colour Fastness to Light**

Grade 4.0 minimum 40 hours

### **Physical properties**

Pilling Class 4  
Breaking Strength warp 167 / weft 173 lbs.  
Seam Slippage warp 103.5 / weft 101.5 lbs.

### **Abrasion**

100.000 cycles Martindale – High Traffic / Public Spaces

### **Benefits of wool**

Wool is a renewable resource  
Wool is very comfortable because of its ability to absorb/  
give off humidity  
Wool is flame retardant  
Wool is biodegradable  
Wool is naturally soil resistant  
Wool ages with grace

### **Quality benefits**

Complies with Möbelfakta  
Very good abrasion  
Good lightfastness  
Flame retardant

### **Environmental benefits**

EU Ecolabel compliant  
Free of intentionally added PFAS  
Mono-material designed for circularity  
REACH compliant  
Californian Proposition 65 list compliant  
LBC Red list compliant  
Healthier Hospitals compliant

### **Green building certificates**

Greenguard Gold: Low chemical emission  
Environmental Product Declaration (EPD): 3rd Party Verified.  
ISO 14025 & EN 15804. Developed in accordance with the  
European standard EN 15804+A2.  
Health Product Declaration (HPD): Declaring textile content  
and substance

### **Country of origin**

United Kingdom

### **Launch**

2021

### **Warranty**

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard  
material is FSC certified and / or contains recycled content.

For further information  
kvadrat.dk