



Mori

Design: Kinnasand

Type: Curtain

Composition: 100% Trevira CS

Yarn type: Staple

Binding: Double leno weave

Width: Approx. 325 cm, 128 inches

Weight: Approx. 340 g/lin.m, 11 oz/ly

Repeat: 34cm H

Colour difference may occur

Cleaning: Washing at max. 60°C.


Drip drying.

Shrinkage approx. 1% / 0% when washed at 60°C.

Ironing might be necessary

Disinfection, see www.kvadrat.dk

More info: Care and maintenance kvadrat.dk



2 year warranty



Mori

Lightfastness

Note 7 ISO 105-B02

Flame resistance

ASTM E84 Class A Unadhered

BS 5867 part 2 type C

CAN ULC S102

CAN ULC S109

DIN 4102 B1

EN 13501-1, B-s1, d0

EN 13 773 class 1

GB 8624 B1

NF P 92 507 M1

NFPA 701

ACT Guidelines Woven fabrics

Flammability

NFPA 701

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 5.0

Wet Crocking: Grade 5.0

Colour Fastness to Light AATCC 16

Grade 4.0 minimum 60 hours

Physical properties

Seam Slippage ASTM D434

Not required fabric under weight

Quality benefits

Very good lightfastness

Permanent flame retardant

Washable

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions
No use of halogen-based flame retardants (incl. brominated and chlorinated)
REACH compliant
Californian Proposition 65 list compliant
LBC Red list compliant
Mono material designed for circularity
Recyclable

Green Building certificates

Greenguard Gold: Low chemical emission
Environmental Product Declaration (EPD): 3rd Party Verified. ISO 14025 & EN 15804. Developed in accordance with the European standard EN 15804+A2.
Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Italy

Warranty

2 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information
kvadrat.dk