



Skydo II

Lightfastness

Note 3-7 ISO 105-B02

Absorption

150 mm airgap

0.35/Class D (flat) EN ISO 354

100 mm airgap

0.35/Class D (flat), 0.60/Class C (waved) EN ISO 354
EN ISO 354

Flame resistance

ASTM E84 Class A unadhered

BS 5867 part 2 type B

CAN ULC S102

CAN ULC S109

DIN 4102 B1

EN 13501-1, B, s1, d0

EN 13 773 class 1

IMO FTP Code 2010 Part 5

IMO FTP Code 2010 Part 7

NFPA 701

ACT Guidelines Woven fabrics

Flammability

NFPA 701

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 5.0

Wet Crocking: Grade 5.0

Colour Fastness to Light AATCC 16

Grade 5.0 minimum 60 hours

Physical properties

Seam Slippage warp 33.5 / weft 19 lbs. ASTM D434

Quality benefits

Dim Out

Acoustic performance

Permanent flame retardant

Washable

Skydo II

Design: Kinnasand

Type: Curtain

Composition: 100% polyester FR

Yarn type: Filament

Binding: Dobby

Width: Approx. 290 cm, 114 inches

Weight: Approx. 550 g/lin.m, 17.7 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Washing at max. 30°C.

Drip drying.

Shrinkage approx. 2% / 2% when washed at 30°C.

Ironing might be necessary

Disinfection, see www.kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year
warranty



0575/27
Acoustic



kvadrat

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions
No use of halogen-based flame retardants (incl. brominated and chlorinated)
REACH compliant
Californian Proposition 65 list compliant
LBC Red list compliant
Mono-material designed for circularity
Recyclable

Green Building certificates

Greenguard Gold: Low chemical emission
Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Japan

Warranty

10 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information
kvadrat.dk