



Hero Heather

Type: Upholstery, panel fabric
Composition: 97% new wool, 3% recycled nylon
Yarn type: Worsted / woollen
Binding: Devon weave
Width: Approx. 140 cm, 55 inches
Weight: Approx. 560 g/lin.m, 18 oz/ly
Repeat: None

Colour difference will occur

Cleaning: Vacuum clean frequently, ideally every week. Remove stains as soon as they occur, with clean warm water or sparkling water. Please be aware that stain removal will cause a darker area as the wool fibers rise when exposed to water. This can only be reduced by gentle atomizing water over the entire furniture. Extraction clean when necessary. Avoid using steam.

More info: Care and maintenance kvadrat.dk



10 year warranty



Hero Heather

Abrasion

Approx. 45.000 Martindale rubs, EN ISO 12947

Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

Pilling

Note 3-4, EN ISO 12945

Seam slippage

Seam parallel to warp: 2.0 mm parallel to weft: 2.5 mm
EN ISO 13 936-2 180 Newton

Lightfastness

Note 6 ISO 105-B02

Fastness to rubbing

Dry note 3-5 ISO 105-X12
Wet note 3-5 ISO 105-X12

Absorption

150 mm airgap
0.65/Class C (flat), 0.90/Class A (waved) EN ISO 354
100 mm airgap
0.55/Class D (flat), 0.80/Class B (waved) EN ISO 354

Airflow

348 Pa s/m EN 29053

Flame resistance

AS/NZS 1530.3
AS/NZS 3837 class 1
ASTM E84 Class A Adhered
ASTM E84 Class A Unadhered
BS 5852 crib 5 with treatment *
BS 5852 part 1
BS 5867 part 2 type B with treatment *
BS 7176 Low Hazard
EN 1021-1/2
EN 13501 B-s2, d0 with treatment *
EN 13 773 class 1 with treatment *
IMO FTP Code 2010 Part 8
NF D 60 013
NFPA 260
NFPA 701 with treatment *
SN 198 898 5.3 with treatment *
UNI 9175 1IM
US Cal. Bull. 117-2013
ÖNORM B1/Q1

Free from added flame-retardant chemicals as standard.

** To pass this test flame retardant treatment is necessary. We are looking into more environmental friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants.*

ACT Guidelines Woven fabrics

Flammability

US Cal. Bull. 117-2013

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 4.0-5.0

Wet Crocking: Grade 3.5-5.0

Colour Fastness to Light AATCC 16

Grade 4.0-5.0 minimum 40 hours

Physical properties

Breaking Strength warp 140 / weft 88 lbs, ASTM D5034

Seam Slippage warp 155 / weft 99.5 lbs, ASTM D4034

Abrasion ASTM D4966

45.000 cycles Martindale – High Traffic / Public Spaces

Quality benefits

Complies with Möbelfakta

Good abrasion

Very good lightfastness

Flame retardant

Acoustic performance

Benefits of wool

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb/
give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

Environmental benefits

EU Ecolabel compliant

Free of intentionally added PFAS

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Healthier Hospitals compliant

No content of PFCs or 'PFAS'

Green building certificates

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content
and substance

Special recommendations

Iron without steam

Country of origin

United Kingdom

Launch

2023

Warranty

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard
material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information

kvadrat.dk