



## Kuri

Design: Margrethe Odgaard

Type: Upholstery, panel fabric

Avoid furniture with hard edges and stackable chairs.

Should never be glued to furniture.

In accordance with California Bill AB 2998 and similar legislations within the United States, this product may not be used as upholstery. It can be used for vertical applications.

Composition: 50% polyurethane, 32% polyester, 12% viscose, 6% silicone

Yarn type: -

Binding: -

Width: Approx. 140 cm, 55 inches

Weight: Approx. 750 g/lin.m, 24 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Wipe regularly with warm water and neutral detergent. Use a clean, soft white cloth or sponge. Do not over saturate the textile or let water pool in seams. If disinfection is required alcohol / ethanol 70-85% or ready to use household bleach is recommended. Chlorine based agents should only be used in extreme conditions as colour might change. UVC disinfection is suitable for all colours. More info, see page 2

After cleaning, rinse repeatedly with cool, clean water. Always pre-test in an invisible area before cleaning.

Do not use solvent-based cleaning agents.

More info: Care and maintenance kvadrat.dk



5 year warranty



## Kuri

### Abrasion

Approx. 100.000 Martindale rubs, EN ISO 12947

*Note: Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.*

### Pilling

Note 5, EN ISO 12945

### Lightfastness

Note 8 ISO 105-B02

### Fastness to rubbing

Dry note 5 ISO 105-X12

Wet note 5 ISO 105-X12

### Resistance to water penetration

>1500 cm = waterproof EN ISO 811

### Flame resistance

AS/NZS 3837 Class 2

ASTM E84 Class B adhered

BS 5852 Crib 5

EN 1021-1/2

IMO FTP Code 2010:Part 8

NF D 60 013

Önorm B1/Q1

UNI 9175 1IM

US Cal. Bull. 117-2013

### ACT Guidelines Coated fabrics

#### Flammability

ASTM E84 Class B adhered

US Cal. Bull. 117-2013

#### Dry & Wet Crocking

Dry Crocking: Grade 4.5-5.0

Wet Crocking: Grade 4.5-5.0

#### Colour Fastness to Light

Grade 4.5 minimum 200 hours

#### Physical properties

Adhesion of coating 4.6/4.3 PASS

Tear strength 8.9 / 22.8 PASS

Breaking strength 139 / 99 PASS

Seam strength (tack tear) 115 / 92 PASS

Flex resistance PASS

Hydrolysis resistance PASS

#### Abrasion

100.000 rubs – High Traffic / Public Spaces

**Environmental benefits**

No harmful siloxanes  
 Formaldehyde free  
 DMF free  
 PFAS free  
 PVC free  
 REACH compliant  
 Californian Proposition 65 list compliant  
 LBC Red list compliant

**Green Building certificates**

Greenguard Gold: Low chemical emission  
 Health Product Declaration (HPD): Declaring textile content and substance

**Country of origin**

China

**Launch:**

2025

**Warranty**

5 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information  
 kvadrat.dk

The Association for Contract Textiles' (ACT) Proposed BIFMA Cleaning Guideline - Assessing

Woven Fabrics for Resistance to Liquid Cleaner and/or Disinfectants

Stain resistance CFFA 141

Colour	Alcohol *slight effect	Household bleach Ex. Oxivir Oxicide Virex	Chlorine bleach max. 10%	Stain resistance
163	Yes	Yes	Yes	Medium
183	Yes	Yes	Yes	Low
193	Yes	Yes	Yes	Medium
203	Yes	Yes	No	Low
223	No	Yes	No	Low
233	Yes	Yes	No	Low
243	Yes	Yes	No	Low
283	Yes	Yes	No	High
323	Yes	Yes	Yes	Low
343	Yes	Yes	Yes	Medium
353	Yes	Yes	Yes	Medium
363	Yes	Yes	Yes	Low
373	Yes	Yes	No	High
393	Yes	Yes	Yes	Medium
773	Yes	Yes	No	Medium
823	Yes	Yes	No	Low
953	Yes	Yes	No	Low
973	Yes	Yes	Yes	High