



## Guest

Design: Louise Sigvardt

Type: Upholstery, panel fabric

*Due to the irregular nature of the chenille yarn, the colour and look will vary, contributing to the natural characteristics of the textile. The pile of the chenille yarn is multi directional giving a varying light reflection over the surface. Colours will appear within a range of tones according to the varying light reflection. Due to the contrasting colours in warp and weft, these changes in light reflection will also affect how the weave is perceived as the warp and weft will appear more or less dominating across the surface. The different directions of the pile appear randomly, giving each piece its own characteristics*

Composition: 100% recycled polyester

Yarn type: Chenille, filament

Binding: Jacquard

Width: Approx. 140 cm, 55 inches

Weight: Approx. 480 g/lin.m, 15 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week if fixed covers. Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. No ironing, only steaming. Steaming might be necessary to remove pressure marks. Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid. Also washable at 60°C, half wash load. Drip drying. Mount in moist condition. Shrinkage app. 1% at 60°C.. Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year warranty



  
**kvadrat**

## Guest

### Abrasion

App. 100.000 Martindale rubs, EN ISO 12947

Colour change: note 4-5 after 6000 rubs

### Pilling

Note 4, EN ISO 12945

### Seam slippage

Seam parallel to warp: 2.5 mm parallel to weft: 3.0 m

EN ISO 13 936-2 180 Newton

### Lightfastness

Note 5-7 ISO 105-B02

### Fastness to rubbing

Dry note 4-5 ISO 105-X12

Wet note 4-5 ISO 105-X12

### Absorption

150 mm airgap

0.70/Class C (flat), 0.85/Class B (waved) EN ISO 354

100 mm airgap

0.60/Class C (flat), 0.75/Class C (waved) EN ISO 354

### Airflow

757 Pa s/m EN 29053

### Flame resistance

AS/NZS 1530.3

AS/NZS 3837 class 2

ASTM E84 Class A Unadhered

ASTM E84 Class A Adhered

BS 5852 Part 1 with treatment \*

BS 5852 Crib 5 with treatment \*

BS 7176 Low Hazard

EN 1021-1/2

IMO FTP Code 2010 : Part 8

NFPA 701 with treatment \*

SN 198 898 5.2 with treatment \*

US Cal. Bull. 117-2013

Free from added flame retardant chemicals as standard

*\* To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now the external finisher may use a treatment containing halogen based flame retardants*

## **ACT Guidelines Woven fabrics**

### **Flammability**

US Cal. Bull. 117-2013

### **Dry & Wet Crocking AATCC 8**

Dry Crocking: Grade 4.5-5.0

Wet Crocking: Grade 4.0-5.0

### **Colour Fastness to Light AATCC 16**

Grade 4.0-5.0 minimum 40 hours

### **Physical properties**

Pilling Class 4 ASTM D4970

Breaking Strength warp 347 / weft 96 lbs. ASTM D5034

Seam Slippage warp 98 / weft 107 lbs. ASTM D 4034

### **Abrasion ASTM D4966**

100.000 cycles Martindale – High Traffic / Public Spaces

### **Quality benefits**

Complies with Möbelfakta

Good abrasion

Very good lightfastness

Washable

### **Environmental benefits**

Complies with EU Ecolabel

Recycled content

Free of intentionally added PFAS

Mono-material designed for circularity

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Healthier Hospitals compliant

### **Green building certificates**

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content and substance

### **Country of origin**

Turkey

### **Launch**

2024

### **Warranty**

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information

kvadrat.dk