



## Memory 2

### Abrasion

Approx. 35.000 Martindale rubs, EN ISO 12947

### Pilling

Note 4, EN ISO 12945

### Seam slippage

Seam parallel to warp: 2.0 mm parallel to weft: 2.0 m  
EN ISO 13 936-2 180 Newton

### Lightfastness

Note 5-8 ISO 105-B02

### Fastness to rubbing

Dry note 4-5 ISO 105-X12  
Wet note 4-5 ISO 105-X12

### Absorption

0.65/Class C (flat), 0.85/Class B (waved) EN ISO 354

### Airflow

2075 Pa s/m EN 29053

### Flame resistance

AS/NZS 3837 class 1  
ASTM E84 Class A Adhered  
ASTM E84 Class A Unadhered  
BS 5852 crib 5 with treatment \*  
BS 7176 Low Hazard  
CAN ULC S102  
CAN ULC S109  
DIN 4102 B1  
EN 1021-1/2  
EN 13501-1, B-s1, d0  
GB 8624 B1  
IMO FTP Code 2010 Part 5  
IMO FTP Code 2010 Part 8  
JIS L 1091 A-1 D  
NF D 60 013  
NF P 92 507 M1  
NFPA 260  
NFPA 701  
ÖNORM B1/Q1  
SN 198 898 5.2  
UNI 9175 1IM  
UNI 9177 Classe 1  
US Cal. Bull. 117-2013

*\* To pass this test flame retardant treatment is necessary.  
We are looking into more environmentally friendly  
alternatives but for now, the external finisher may use a  
treatment containing halogen-based flame retardants*

### Memory 2

Design: Patricia Urquiola

Type: Upholstery, panel fabric

*In accordance with California Bill AB 2998 and similar  
legislation within the United States, this product may not be  
used as upholstery. It can be used for vertical applications.*

Composition: 100% Trevira CS

Yarn type: Filament

Binding: Jacquard

Width: Approx. 140 cm, 55 inches

Weight: Approx. 650 g/lin.m, 21 oz/ly

Repeat: Approx. 144 cm, 56.5 inches V / 140 cm, 55 inches H

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week  
if fixed covers. Remove stains as soon as they occur, with  
clean warm water or sparkling water. Extraction clean when  
necessary. Extraction cleaning might dissolve water-based  
glue. Pay attention to temperature and amount of cleaning  
fluid.

Also washable at 60-80°C, half wash load. Drip drying.

Mount in moist condition. Shrinkage app. 2% at 60°C.

Be aware of increased shrinking and creasing the higher the  
temperature.

Disinfection, see kvadrat.dk

More info: Care and maintenance - kvadrat.dk



10 year  
warranty



# kvadrat

## **ACT Guidelines Woven fabrics**

### **Flammability**

US Cal. Bull. 117-2013

### **Dry & Wet Crocking**

Dry Crocking: Grade 5.0

Wet Crocking: Grade 5.0

### **Colour Fastness to Light**

Grade 4.0 minimum 40 hours

### **Physical properties**

Pilling Class 4

Breaking Strength warp 319 / weft 191 lbs.

Seam Slippage warp 133 / weft 150 lbs.

### **Abrasion**

35.000 cycles Martindale – Low Traffic / Private Spaces

### **Quality benefits**

Good abrasion

Very good lightfastness

Permanent flame retardant

Washable

### **Environmental benefits**

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

No use of halogen-based flame retardants (incl. brominated and chlorinated)

Free of intentionally added PFAS

Mono-material designed for circularity

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

### **Green building certificates**

Greenguard Gold: Low chemical emission

Environmental Product Declaration (EPD): 3rd Party Verified.

ISO 14025 & EN 15804. Developed in accordance with the European standard EN 15804+A2.

Health Product Declaration (HPD): Declaring textile content and substance

### **Country of origin**

Holland

### **Launch**

2013

### **Warranty**

10 years. See terms and conditions on [kvadrat.dk](http://kvadrat.dk)

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information

[kvadrat.dk](http://kvadrat.dk)