



# Technicolour

## Abrasion

Approx. 80.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention*

## Pilling

Note 4, EN ISO 12945

## Seam slippage

Seam parallel to warp: 10.0 mm parallel to weft: 8.1 mm  
EN ISO 13 936-2 180 Newton

## Lightfastness

Note 6-7 ISO 105-B02

## Fastness to rubbing

Dry note 4-5 ISO 105-X12  
Wet note 3-5 ISO 105-X12

## Absorption

0.50/Class D (flat), 0.75/Class C (waved)

## Airflow

301 Pa s/m EN 29053

## Flame resistance

AS/NZS 15303.  
AS/NZS 3837 class 2  
ASTM E84 Class A Unadhered  
ASTM E84 Class A Adhered  
BS 5852 crib 5 with treatment \*  
BS 5852 part 1  
BS 5867 Part 2 type B with treatment \*  
BS 7176 Low Hazard  
EN 1021-1/2  
IMO FTP Code 2010 Part 8  
NF D 60 013  
NFPA 701 with treatment (AB 2998 compliant)  
SN 198 898 5.3 with treatment \*  
UNI 9175 1IM  
US Cal. Bull. 117-2013

Free from added flame retardant chemicals as standard

*\* To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants*

## Technicolour

Design: Peter Saville

Type: Upholstery, panel fabric

Composition: 100% English wool

Yarn type: Worsted

Binding: Plain

Width: Approx. 140 cm, 55 inches

Weight: Approx. 430 g/lin.m, 14 oz/ly

Due to the structure of the yarn's irregularities will occur  
Foreign fibers will occur

Colour difference will occur

Cleaning: Vacuum clean frequently, ideally every week.  
Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid.  
Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year warranty



# kvadrat

## **ACT Guidelines Woven fabrics**

### **Flammability**

US Cal. Bull. 117-2013

### **Dry & Wet Crocking**

Dry Crocking: Grade 4.5-5.0

Wet Crocking: Grade 3.0-5.0

### **Colour Fastness to Light**

Grade 4.0-5.0 minimum 40 hours

### **Physical properties**

Pilling Class 4

Breaking Strength warp 133 / weft 131 lbs.

Seam Slippage warp 26 / weft 24 lbs.

### **Abrasion**

80.000 cycles Martindale – High Traffic / Public Spaces

## **Quality benefits**

Complies with Möbelfakta

## **Environmental benefits**

EU Ecolabel compliant

Free of intentionally added PFAS

Mono-material designed for circularity

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Healthier Hospitals compliant

## **Green building certificates**

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content and substance

## **Country of origin**

United Kingdom

## **Launch**

2025

## **Warranty**

10 years. See terms and conditions on [kvadrat.dk](https://www.kvadrat.dk)

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information

[kvadrat.dk](https://www.kvadrat.dk)