



Super Felt

Lightfastness

Note 5-8 ISO 105-B02

Absorption

150 mm airgap

0.40/ Class D (flat), 0.6/Class C (waved) EN ISO 354

100 mm airgap

0.4/ Class D (flat), 0.55/Class D (waved) EN ISO 354

Airflow

131 Pa s/m EN 29053

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

Free of intentionally PFAS

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Recyclable

Special recommendations

When hanging, the curtain should touch the ground.

Country of origin

Italy

Launch

2026

Warranty

2 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information

kvadrat.dk

Super Felt

Design: Kvadrat Residential

Type: Curtain

Composition: 100% wool

Yarn type: Spun

Binding: Jacquard

Width: Approx. 165cm, 11"

Weight: Approx. 350 g/m, 18 oz/y

Repeat: None

Colour difference may occur

Cleaning: Follow the ISO symbols

Drip drying

Shrinkage warp approx. 0%, weft approx. 0%

Ironing might be necessary.

Disinfection, see www.kvadrat.dk

Due to the composition of natural fibres the curtain can hang longer depending on the height of the curtain, room temperature and humidity.

This might also happen for textiles woven in a very open construction or knitted textiles.

It is therefore recommended to avoid the use of weight, but an adjustment of the length might still be needed after a while. Also, a possibility to let the curtain touch the ground when hanging.

More info: Care and maintenance kvadrat.dk



2 year
warranty

kvadrat