




Steelcut Quartet

Design: Frans Dijkmeijer & Giulio Ridolfo

Type: Upholstery

Composition: 90% new wool, 10% nylon

Yarn type: Worsted

Binding: Semi-plain

Width: Approx. 140 cm, 55 inches

Weight: Approx. 770 g/lin.m, 24.8 oz/ly

Repeat: None

Foreign fibres may occur

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week.
Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid.

Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year
warranty



0575/28

Acoustic



Steelcut Quartet

Abrasion

Approx. 100.000 Martindale rubs, EN ISO 12947

Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention

Pilling

Note 4-5, EN ISO 12945

Seam slippage

Seam parallel to warp: 3.5 mm parallel to weft: 2.0 m

Lightfastness

Note 6-7 ISO 105-B02

Fastness to rubbing

Dry note 4-5 ISO 105-X12

Wet note 4-5 ISO 105-X12

Absorption

0.70/Class C (flat), 0.95/Class A (waved) EN ISO 354

Airflow

910 Pa s/m EN 29053

Flame resistance

AS/NZS 1530.3

AS/NZS 3837 class 2

ASTM E84 Class B adhered

ASTM E84 Class A unadhered

BS 5852 Crib 5 with treatment *

BS 5852 Part 1

BS 7176 Low Hazard

BS EN 13501-1 B, s2 d1 with treatment *

EN 1021-1/2

IMO FTP Code 2010:Part 8

NF D 60 013

NFPA 260

NFPA 701 with treatment (AB 2998 compliant)

ÖNORM B1/Q1

SN 198 898 5.3 with treatment *

UNI 9175 1IM

US Cal. Bull. 117-2013

Free from added flame-retardant chemicals as standard

** To pass this test flame retardant treatment is necessary.
We are looking into more environmental friendly alternatives
but for now the external finisher may use a treatment
containing halogen based flame retardants*

kvadrat

ACT Guidelines Woven fabrics

Flammability

US Cal. Bull. 117-2013

Dry & Wet crocking

Dry Crocking: Grade 4.5-5.0

Wet Crocking: Grade 4.0-5.0

Colour Fastness to Light

Grade 4.5-5.0 40 hours

Physical properties

Pilling Class 4-5

Breaking strength warp 263 / weft 142 lbs.

Seam slippage warp 127 / weft 58 lbs.

Abrasion

100.000 cycles Martindale – High Traffic / Public Spaces

Quality benefits

Complies with Möbelfakta

Environmental benefits

EU Ecolabel compliant

No use of halogen-based flame retardants (incl. brominated and chlorinated)

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Healthier Hospitals compliant

Green building certificates

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

United Kingdom

Warranty

10 years. See terms and conditions on kvadrat.dk

Launch

2022

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information

[kvadrat.dk](https://www.kvadrat.dk)

kvadrat