



Outer View

Lightfastness

Note 5-8 ISO 105-B02

Absorption

150 mm airgap

0.15/Class E (flat), 0.25/Class E (waved) EN ISO 354

100 mm airgap

0.15/Class E (flat), 0.25/Class E (waved) EN ISO 354

Airflow

24 Pa s/m EN 29053

Flame resistance

AS/NZS 1530.3

BS 5867 part 2 type B

Cal. Title 19, Sec. 1237.1

DIN 4102 B1

EN 13 773 class 1

IMO FTP Code 2010 Part 7

NF P 92 507 M1

NFPA 701

SN 198 898 5.2

UNI 9177 Classe 1

ACT Guidelines Woven fabrics

Flammability

NFPA 701

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 5

Wet Crocking: Grade 4

Colour Fastness to Light AATCC 16

Grade 4 minimum 60 hours

Outer View

Design: Teruhiro Yanagihara

Type: Curtain

Composition: 70% recycled polyester FR, 30% polyester FR

Yarn type: Filament, Spun

Binding: Plain

Width: Approx. 303 cm, 119 inches

Weight: Approx. 640 g/lin.m, 21 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Washing at max. 60°C.

Drip drying.

Shrinkage warp approx. 2%, weft approx. 2% when washed at 60°C.

Ironing might be necessary.

Disinfection, see www.kvadrat.dk

More info: Care and maintenance kvadrat.dk



10 year
warranty



kvadrat

Environmental benefits

EU Ecolabel complaint

No use of halogen-based flame retardants (incl. brominated and chlorinated)

No intentionally added PFAS

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Mono material designed for circularity

Recyclable

Green Building certificates

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Turkey

Launch

2026

Warranty

10 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information

kvadrat.dk

kvadrat