

For the Account of

Kvadrat A/S
Lundbergsvej 10
8400 Ebeltoft Denmark

Client's Identification

DAWN 2

CERTIFICATE OF TESTING

TEST PERFORMED FAR Part 25.853 (a)(1)(ii), Appendix F, Part I (b)(4) – 12 Second Vertical Test

TEST RESULTS

Specimen	Afterflame (s)	Drip Burn (s)	Char Length (in)
1	0.0	0.0	3.1
2	9.0	0.0	3.4
3	0.0	0.0	3.5
Avg. Warp	3.0	0.0	3.3
Specimen	Afterflame (s)	Drip Burn (s)	Char Length (in)
1	0.0	0.0	3.9
2	0.0	0.0	3.5
3	0.0	0.0	3.6
Avg. Fill	0.0	0.0	3.7

Tested:

- ☒ Initially
☐ After Laundering
☐ After Dry Cleaning

NOTES

Test Conditions 70 ±4°F, 65 ±5% Relative Humidity *requirement is 70 ±5°F and 50 ±5% relative humidity*
Sampling As Received

ACCEPTANCE CRITERIA

1. Average Burn Length cannot exceed **8 inches** maximum average.
2. Average Flame Time after removal of the flame source may not exceed **15 seconds**.
3. Drippings from the test specimen may not continue to flame for more than an average of **5 seconds** after falling.
4. Melt Length, when observed, is reported, however, it is not factored into the acceptance criteria.

CONCLUSION

Based on the above Results and Acceptance Criteria, the item tested:

- ☒ Complies
☐ Does Not Comply

CERTIFICATION I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above.

Berta Stiver

Authorized Signature

Date Order Completed: 09/17/2026