Canvas 2
Design: Giulio Ridolfo

Type: Upholstery, panel fabric
Composition: 90% wool, 10% nylon
Yarn type: Worsted
Binding: Plain variant
Width: Approx. 140 cm, 55 inches
Weight: Approx. 480 g/lin.m, 15.4 oz/ly
Repeat: None

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week. Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water-based glue. Pay attention to temperature and amount of cleaning fluid.

Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk

10 year warranty

Canvas 2

Abrasion
Approx. 100.000 Martindale rubs, EN ISO 12947

Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention

Pilling
Note 4 EN ISO 12945

Seam slippage
Seam parallel to warp: 3.5 mm parallel to weft: 2.0 mm
EN ISO 13 936-2 180 Newton

Lightfastness
Note 5-6 ISO 105-B02

Fastness to rubbing
Dry note 4-5 ISO 105-X12
Wet note 4-5 ISO 105-X12

Absorption
0.60/Class C (Flat), 0.80/Class B (Waved) EN ISO 354

Airflow
849 Pa s/m EN 29053

Flame resistance
AS/NZS 1530.3
ASTM E84 Class A Adhered
ASTM E84 Class A Unadhered
BS 5852 crib 5 with treatment *
BS 5852 ignition source 3
BS 5852 part 1
BS 7176 Low Hazard
EN 1021-1/2
EN 13501 B-s2, d0 wrapped, with treatment *
IMO FTP Code 2010 Part 8
NF D 60 013
NFPA 260
NFPA 701 with treatment
ÖNORM B1/Q1
SN 198 898 5.3 with treatment *
UNI 9175 1IM
US Cal. Bull. 117-2013

Free from added flame-retardant chemicals as standard

** To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants*

kvadrat

ACT Guidelines Woven fabrics

Flammability
US Cal. Bull. 117-2013

Dry & Wet Crocking
Dry Crocking: Grade 5.0
Wet Crocking: Grade 4.5

Colour Fastness to Light
Grade 4.0 minimum 40 hours

Physical properties
Pilling Class 4
Breaking Strength warp 143 / weft 171 lbs.
Seam Slippage warp 167 / weft 37 lbs.

Abrasion
100.000 cycles Martindale – High Traffic / Public Spaces

Quality benefits
Complies with Möbelfakta

Environmental benefits
EU Ecolabel compliant
Free of intentionally added PFAS
REACH compliant
Californian Proposition 65 list compliant
LBC Red list compliant
Healthier Hospitals Compliant

Green building certificates
Greenguard Gold: Low chemical emission
Environmental Product Declaration (EPD): 3rd Party Verified. ISO 14025 & EN 15804. Developed in accordance with the European standard EN 15804+A2.
Health Product Declaration (HPD): Declaring textile content and substance

Country of origin
United Kingdom

Launch
2012

Warranty
10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information
kvadrat.dk

kvadrat