

Divina
Design: Finn Sködt

Type: Upholstery
Composition: 100% wool
Yarn type: Woolen
Binding: Broken twill
Width: Approx. 140 cm, 55 inches
Weight: Approx. 780 g/lin.m, 25 oz/ly
Repeat: None
Foreign fibers may occur

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week. Remove stains as soon as they occur, with clean warm water or sparkling water. Please be aware that stain removal will cause a darker area as the wool fibers rise when exposed to water. This can only be reduced by gentle atomizing water over the entire furniture.
Extraction clean when necessary. Avoid using steam.

More info: Care and maintenance kvadrat.dk

10 year warranty

Divina

Abrasion
Approx. 45.000 Martindale rubs, EN ISO 12947

Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention

Pilling
Note 3 EN ISO 12945

Seam slippage
Seam parallel to warp: 2.0mm parallel to weft: 2.0 mm
EN ISO 13 936-2 180 Newton

Lightfastness
Note 4-7 ISO 105-B02

Fastness to rubbing
Dry note 4-5 ISO 105-X12
Wet note 3-5 ISO 105-X12

Absorption
150 mm airgap
0.65/Class C (flat), 0.90/Class A (waved) EN ISO 354
100 mm airgap
0.55/Class D (flat), 0.85/Class B (waved) EN ISO 354

Airflow
380 Pa s/m EN 29053

kvadrat

Flame resistance
AS/NZS 1530.2
AS/NZS 1530.3
AS/NZS 3837 Class 2
ASTM E84 Class A Adhered
ASTM E84 Class B Unadhered
ASTM E84 Class A Unadhered with treatment *
BS 5852 Crib 5
BS 5852 part 1
EN 1021-1/2
EN 13501, C-s1, d0, glued
EN 13501 B-s2, d0 wrapped, with treatment *
GB 50222 B1 with treatment (Chinese) *
IMO FTP Code 2010 Part 8
NF D 60 013
NFPA 260
ÖNORM B1/Q1
SN 198 898 5.3 with treatment *
UNI 9175 1IM
US Cal. Bull. 117-2013

Free from added flame-retardant chemicals as standard

** To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants*

ACT Guidelines Woven fabrics

Flammability
US Cal. Bull. 117-2013

Dry & Wet Crocking
Dry Crocking: Grade 4.5-5.+
Wet Crocking: Grade 4.0-5.0

Colour Fastness to Light
Grade 4.0-5.0, minimum 40 hours

Physical properties
Pilling Class 3
Breaking Strength warp 100 / weft 82 lbs.
Seam Slippage warp 98.5 / weft 79 lbs.

Abrasion
45.000 cycles Martindale – High Traffic / Public Spaces

Quality benefits
Complies with Möbelfakta

Environmental benefits
EU Ecolabel compliant
Free of intentionally added PFAS
REACH compliant
Californian Proposition 65 list compliant
LBC Red list compliant
Healthier Hospitals Compliant

Green building certificates
Greenguard Gold: Low chemical emission
Environmental Product Declaration (EPD): Based on a LCA following EN 15804 and follow the standard of ISO 14040
Health Product Declaration (HPD): Declaring textile content and substance

Country of origin
United Kingdom

Launch
1984

Warranty
10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information
kvadrat.dk

kvadrat



Divina
Design: Finn Sködt

Type: Curtain
D*ue to the natural properties of wool, Divina may stretch immediately or over time, when used as a curtain, depending on the curtain height and the indoor climate. We recommend allowing for additional fitting or adaption to accommodate potential stretching.*

Composition: 100% wool
Yarn type: Woolen
Binding: Broken twill
Width: Approx. 140 cm, 55 inches
Weight: Approx. 780 g/lin.m, 25 oz/ly
Repeat: None
Foreign fibers may occur

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week. Remove stains as soon as they occur, with clean warm water or sparkling water. Please be aware that stain removal will cause a darker area as the wool fibers rise when exposed to water. This can only be reduced by gentle atomizing water over the entire curtain or steaming the curtain.
Avoid steam when ironing.

More info: Care and maintenance kvadrat.dk

10 year warranty

Divina

Lightfastness
Note 4-7 ISO 105-B02

Absorption
150 mm airgap
0.65/Class C (flat), 0.90/Class A (waved) EN ISO 354
100 mm airgap
0.55/Class D (flat), 0.85/Class B (waved) EN ISO 354

Airflow
380 Pa s/m EN 29053

Flame resistance
AS/NZS 1530.2
AS/NZS 1530.3
AS/NZS 3837 Class 2
ASTM E84 Class A Adhered
ASTM E84 Class B Unadhered
ASTM E84 Class A Unadhered with treatment *
BS 5867 part 2 type B
CAN ULC S109 with treatment *
EN 13501, C-s1, d0, glued
EN 13501 B-s2, d0 wrapped, with treatment *
EN 13773 class 1 with treatment *
GB 50222 B1 with treatment (Chinese) *
NFPA 701 with treatment *
ÖNORM B1/Q1
SN 198 898 5.3 with treatment *

Free from added flame-retardant chemicals as standard

** To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants*

kvadrat

Special recommendations
Due to the natural properties of wool, Divina may stretch immediately or over time, when used as a curtain, depending on the curtain height and the indoor climate. We recommend allowing for additional fitting or adaption to accommodate potential stretching.
When exposed to strong sunlight, we recommend using a lining to protect the wool fibres from deterioration caused by prolonged heat exposure.

Curtain fullness
Divina is 140 cm wide. We recommend 120% fullness, calculated by multiplying the finished curtain width by 2.2 to determine the amount of fabric required.

Wave curtain confectioning
Divina is a fray-resistant textile. We therefore recommend using clean-cut edges for the finishing details.

Top finish:

- Wave pleat heading, with the option of an additional fabric inlay
- The top edge can be either folded or clean-cut

Side finish

- Clean-cut edges, without folding or hemming

Vertical seams/Fabric joins

- Clean-cut fabric edges with a flat overlap of approx. 2 cm
- Double stitch construction ensures a clean, consistent finish on both sides of the curtain
- To allow for future height adjustment, vertical seams may be finished a few centimeters above the bottom edge. This ensures that the curtain can be shortened later without compromising or damaging the vertical seams.

Environmental benefits
EU Ecolabel compliant
Free of intentionally added PFAS
REACH compliant
Californian Proposition 65 list compliant
LBC Red list compliant
Healthier Hospitals Compliant

Green building certificates
Greenguard Gold: Low chemical emission
Environmental Product Declaration (EPD): Based on a LCA following EN 15804 and follow the standard of ISO 14040
Health Product Declaration (HPD): Declaring textile content and substance

Country of origin
United Kingdom

Launch
1984

Warranty
10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information
kvadrat.dk

kvadrat