

Twilight
Design: Patricia Urquiola

Type: Dim-out curtain
Composition: 59% polyester FR, 41% polyester
Yarn type: Filament
Binding: Satin
Width: Approx. 300 cm, 118 inches
Weight: Approx. 1080 g/lin.m, 34.8 oz/ly
Repeat: none

Colour difference may occur

Cleaning: Washing at max. 60°C.
Drip drying.
Shrinkage approx. 1% / 1% when washed at 60°C.
Ironing might be necessary.
Disinfection, see kvadrat.dk

More info: Care and maintenance kvadrat.dk

10 year warranty

Twilight

Lightfastness
Note 6-8 ISO 105-B02

Light Reflection DIN EN 410
8-48% (test is performed in flat state)

Light Transmission DIN EN 410
0-0.8% (test is performed in flat state)

Absorption
100 mm airgap
0.55/Class D (flat), 0.80/Class B (waved) EN ISO 354

Airflow
1374 Pa s/m EN 29053

Flame resistance
AS/NZS 1530.2
AS/NZS 1530.3
AS/NZS 3837
ASTM E84 Class A Adhered
ASTM E84 Class A Unadhered
BS 5867 part 2 type B
DIN 4102 B1
EN 13 773 class 1
EN 13501 B-s1, d0
IMO FTP Code 2010 Part 7
JIS L 1091 A-1 D
NFPA 701
SN 198 898 5.1
UNI 9177 Classe 1

ACT Guidelines Woven fabrics

Flammability
NFPA 701

Dry & Wet Crocking AATCC 8
Dry Crocking: Grade 4.5
Wet Crocking: Grade 4.5

Colour Fastness to Light AATCC 16
Grade 4.5 minimum 60 hours

Physical properties
Seam Slippage warp 25 / weft 25.5 lbs. ASTM D434

kvadrat

Quality benefits
+ 99% dim-out
Good lightfastness
Permanent flame retardant
Washable
Acoustic performance

Environmental benefits
Complies with EU Ecolabel
REACH compliant
Californian Proposition 65 list compliant
LBC Red list compliant
Healthier Hospitals compliant

Green Building certificates
Greenguard Gold: Low chemical emission
Health Product Declaration (HPD): Declaring textile content and substance

Country of origin
Turkey

Launch
2015

Warranty
10 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information
kvadrat.dk

kvadrat