Test Report

Report Number: 951905-2-TEX

Assignor:



DANISH TECHNOLOGICAL INSTITUTE

Gregersensvej 1 DK-2630 Taastrup +45 72 20 20 00 info@teknologisk.dk

www.teknologisk.dk

Page 1 of 3 Init.: CHF/LELN Order no.: 951905

Encl.: 2

Kvadrat A/S, Lundbergsvej 10 , DK-8400 Ebeltoft

Material: Upholstery fabric. See enclosure A for detailed sample description.

Sampling: The assignor confirms having selected the product. The product was forwarded by the

assignor and received at Danish Technological Institute on 3 November 2020.

Period: The test took place from 4 November 2020 to 13 November 2020.

Method: The test methods used are referenced in connection with the results. See enclosure B.

Test results: The results are shown in enclosure B.

Terms: This test was conducted accredited in accordance with international requirements (ISO/IEC

17025:2017) and in accordance with the General Terms and Conditions of Danish

Technological Institute. The test results solely apply to the tested item. This test report may be quoted in extract only if Danish Technological Institute has granted its written consent.

Place: Danish Technological Institute, Taastrup, Building and Construction

Signature: This document is only valid with a digital signature from Danish Technological Institute. The

date of issue appears from the digital signature.

Charlotte Fischer Senior Consultant










Sample

Description: Upholstery fabric

Designated: Ara 724

Fibre content: 92% new wool, worsted, 8% nylon Approximate mass per area unit: 357 g/m².

Photo:





Results

Test of Upholstery fabric

Determination of the abrasion resistance of fabrics by the Martindale method

Part 2: Determination of specimen breakdown

EN ISO 12947-2:2016

Test conditions: 21°C, 65% RH

Colour change: DS EN 20105-A02:1997/ISO 105-A02/cor2:2005:1997 (1-5 scale, 5 best rating)

Pre-treatment	Test parameters	Results
		[rubs]
(none)	Mass: 795 g	80 000
	Nominal pressure: 12 kPa	70 000
	End-point: Two broken threads	85 000
		End result: 70 000
		Colour change: Note 4-5
		after 6000 rubs