

Received: 05/11/2007	Completed: 05/18/2007	Letter: V	rb	P.O.#:	Test Report #:	2-67707-0-
Client's Identification	Style: Steelcut Trio by Kvadrat					
Tested For:	<b>kvadrat</b> DK - 8400 Ebeltoft		Key Test: NFPA 260 Cover Fabric (BLDG)		85	
				Tel: 1-(212)-614-2977	Ext:	
				Fax: 1-(212)-982-9221		

PC: 4H /jd

TEST PERFORMED: NFPA 260 Standard Methods of Tests and Classification System for Cigarette Ignition Resistance of Components of Upholstered Furniture; Cover Fabric Test

RESULTS:	TEST		RETEST (If Required)	
	Ignition (yes/no/SE)	Char Length On Vertical Panel (mm)	Ignition (yes/no/SE)	Char Length On Vertical Panel (mm)
Specimen #				
1	SE	10	SE	12
2	SE	10	No	10
3	SE	8	SE	10

ABBREVIATION WHICH MAY BE USED:

SE: Indicates that the cigarette self extinguished prior to burning its entire length. When this occurs, a "retest" of that specimen is performed.

REMARKS: None.

CLASSIFICATION SYSTEM:

Class I - For each specimen: No obvious ignition; maximum char length 45 mm (1.75").  
(Indicates propensity to resist cigarette ignition in conjunction with standard foam filling material.)

Class II - For any specimen: Obvious ignition; or char length exceeding 45 mm (1.75").  
(Indicates inability to resist cigarette ignition in conjunction with standard foam filling material.)

CONCLUSION: Based on the above Results and Classification System, the item tested is assigned a:

Class I rating;     Class II rating

Received:05/11/2007	Completed:05/18/2007	Letter: V	rb	P.O.#:	Test Report #:	2-67707-0-
Client's Identification	Style: Steelcut Trio by Kvadrat					
Tested For:	<b>kvadrat</b> DK - 8400 Ebeltoft		Key Test: NFPA 260 Cover Fabric (BLDG)			85
			Tel: 1-(212)-614-2977		Ext:	
			Fax: 1-(212)-982-9221			

CODE INFORMATION: In accordance with --

- (1) The 2006 Edition of the NFPA Life Safety Code 101 paragraph 10.3.2.1(1);
- (2) The 2006 Edition of the International Fire Code, paragraph 805.1.1.1, 805.2.1.1 and 805.3.1.1

Upholstered furniture components shall be Class I when tested in accordance with NFPA 260, when used in:

- Detention or correctional occupancy
- Health care occupancy
- Residential board & care occupancy

In certain situations an exception is made if the rooms or areas are sprinklered.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by NFPA 260.

*Heather E. Robertson*

AUTHORIZED SIGNATURE  
THE GOVMARK ORGANIZATION, INC. /rb

**MS. HEATHER ROBERTSON**

(Page 2 of 2)