

96-D Allen Boulevard Farmingdale, New York 11735-5626 USA Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956 e-mail: info@govmark.com

Page 1

PC: 4H /jd

TEST PERFORMED: NFPA 260 Standard Methods of Tests and Classification System for Cigarette Ignition Resistance of Components of Upholstered Furniture; Cover Fabric Test

| RESULTS: | TEST | | RETEST (If Required) | | | |
|------------|---|----|-------------------------|--|--|--|
| Specimen # | Char Length Ignition On Vertical (yes/no/SE) Panel (mm) | | Ignition (yes/no/SE) | Char Length On Vertical Panel (mm) | | |
| | | | | | | |
| 1 | SE | 10 | SE | 10 | | |
| 2 | SE | 10 | SE | 10 | | |
| 3 | SE | 10 | SE | 10 | | |

ABBREVIATION WHICH MAY BE USED:

SE: Indicates that the cigarette self extinguished prior to burning its entire length. When this occurs, a "retest" of that specimen is performed.

REMARKS: None.

CLASSIFICATION SYSTEM:

- Class I For each specimen: No obvious ignition; maximum char length 45 mm (1.75"). (Indicates propensity to resist cigarette ignition in conjunction with standard foam filling material.)
- Class II For any specimen: Obvious ignition; or char length exceeding 45 mm (1.75"). (Indicates inability to resist cigarette ignition in conjunction with standard foam filling material.)

CONCLUSION: Based on the above Results and Classification System, the item tested is assigned a:

[x] Class I rating; [] Class II rating

(Page 1 of 2)



96-D Allen Boulevard Farmingdale, New York 11735-5626 USA Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956 e-mail: info@govmark.com

Page 2

| Received:04/30 | 0/2008 Completed: 05/06/2008 | Letter: F3 | rb | P.O.#: | | Test Report #: | | 2-73356-3- |
|----------------------------|------------------------------|------------|----|--|--|----------------|-----|------------|
| Client's Identification | Style: Remix by Kvadrat. | | | | | | | |
| Tested For: | For: OK - 8400 Ebeltoft | | | Key Test: NFPA 260 Cover Fabric (BLDG) Tel: 1-(631)-851-3342 Ext: Fax: 1-(631)-342-0264 | | | 105 | |

CODE INFORMATION: In accordance with --

(1) The 2006 Edition of the NFPA Life Safety Code 101 paragraph 10.3.2.1(1);

(2) The 2006 Edition of the International Fire Code, paragraph 805.1.1.1, 805.2.1.1 and 805.3.1.1

Upholstered furniture components shall be Class I when tested in accordance with NFPA 260, when used in:

Detention or correctional occupancy Health care occupancy Residential board & care occupancy

In certain situations an exception is made if the rooms or areas are sprinklered.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by NFPA 260.

AUTHORIZED SIGNATURE

THE GOVMARK ORGANIZATION, INC. /jb MS. HEATHER POBERTSON

Leather G. Rebertsos

(Page 2 of 2)

The results contained in this report relate only to item(s) tested. The test report shall not be reproduced, except in full, without written approval from The Govmark Organization, Inc.