





DANISH TECHNOLOGICAL INSTITUTE

Test Report no. A 453371-11

Gregersensvej DK-2630 Taastrup Tel. +45 72 20 20 00 Fax +45 72 20 20 19

info@teknologisk.dk www.teknologisk.dk

Kvadrat A/S, Lundbergsvej 10, 8400 Ebeltoft		
Test material: Upholstery fabric, Sunniva		
Design:	Received: 20-10-2011 Completed: 27-10-2011	
Fibre content: 62% new wool, 25% viscose, 8% flax, 5% polyamide (Manufacturer's information)	Sample no.: 453371-11	
Care label: (Not given)	Your ref.: Lone Henriksen	

Test Methods	Results	
Determination of the slippage resistance of yarns at a seam in woven fabrics - Fixed load method ISO/FDIS 13936-2:2004 Performed on: Standard seam Load: 180 N	Average of 5 determinations Seam parallel to warp: Seam parallel to weft:	9,5 mm seam opening 8 mm seam opening

The test has been performed according to the attached conditions, which are according to the guidelines laid down by DANAK (The Danish Accreditation). The testing is only valid for the tested specimen. The test report may only be extracted, if the laboratory has approved the extract.

This report was generated by software version 2.41 of 2010-12-23.

27 October 2011, Danish Technological Institute, Textile

Penette Berner Hansen Ph. Direct: +45 72 20 21 39 E-mail: jeanette berner hansen@teknologisk.dk

Test responsible

Co-reader