

# Investigation report

### **SAHCO GmbH**

Fr. Sarah Kemmerer Kreuzburger Str 17-19

90471 Nürnberg

**DELCOTEX** 

Delius Techtex GmbH & Co. KG Vilsendorfer Str. 50 33739 Bielefeld

Germany

Homepage: www.textillabor.eu

Contact: Division: Detlef von Seyfried Laboratory/ Lab Manager

Phone:

+49 (0) 52 06 / 91 07 - 57

Fax:

+49 (0) 52 06 / 91 07 - 34

Date:

07.05.2019

## Investigation report No. 18-E-338.5

order description:

Determination of fabric propensity to surface fuzzing and to pilling - Part 2:

Modified Martindale method ISO 12945 (2000-11) in according to DIN EN 14465

(2006-09) Specification Upholstery fabric

sample:

Velour, Tepice; brandname Jade 600629

sampling:

by orderer

orderer:

see address

date of order:

03.05.2018

date of delivery:

20.06.2018

date of testing:

29.06.2018

number of pages:

2

#### Remark:

The results are valid only for the tested object. Accredited test methods are underlined. The valuations and Interpretations in the investigation report are not subject to accreditation. Tests conducted through co-operation partners are marked with °. The content of this investigation report will not be passed to third persons without written approval of the orderer. The partial publication of the test report, as well as the usage for commercial process, is only allowed with a permission of the DELCOTEX Delius Techtex GmbH & Co. KG. Remnants of test material will be destroyed after 3 months. Previously stated specifications / data sheets / certificates are only characters and no warranties. Also no warranty in case of durability will be overtaken. Finally our general delivery and payment conditions are valid (please see www.textillabor.eu).



## Investigation report No. 18-E-338.5

page 2 of 2

## Instructions for performing

 Method: Determination of fabric propensity to surface fuzzing and to pilling- Part 2:Modified Martindale method ISO 12945 (2000-11) in according to DIN EN 14465 (2006-09)

## 2. Measuring conditions

tester:

Martindale-tester

abrasive:

wool-abrasive

pressure weight:

415 +/- 2 g

test temperature:

20 +/- 2 °C

test humidity:

65 +/- 4 %

number of specimen:

3

number of observers:

2

pretreatment:

No

## Test results

Article:

Velour, Tepice; brandname Jade 600629

Number of cycles	Mark*
500	4-5
1.000	4-5
2.000	4
5.000	4

**Remark:** According to DIN EN 14465 (2006-09) the article, in reference to seam slippage resistance in furnishing fabrics, the article is ranked within **category B.** 

i. A. Detlef von Seyfried

Labor/Laboratory

DELCOTEX Delius Techtex GmbH & Co. KG

Only the information contained in the signed test report is binding.