

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

TEST REPORT

Client : Kvadrat Lundber Ebeltoft Denmark	gsvej 10 8400	Test Number : Issue Date : Print Date :	4/05/202	1	
Sample Descriptior	Clients Ref : "Seaside" Woven fabric Colour : Linen End Use : Drapery Nominal Composition : 82% Linen, 6% Polyester, 4% Viscose, 4% Cotton, 4% Acrylic Nominal Mass per Unit Area/Density : Approx 100g/m2 Nominal Thickness : Approx 0.5mm				
AS/NZS 1530.3-1999 Methods for Fire Tests on Building Materials, Components and Structures Part 3: Simultaneous Determination of Ignitability, Flame Propagation, Heat Release and Smoke Release					
	Face tested:	Face			
	Date tested:	04-05-2021			
		Standard Error	Mean		
	Ignition time	1.01	11.21	min	
	Flame propagation time	Nil	Nil	sec	
	Heat release integral	0.7	7.6	kJ/m²	
	Smoke release, log d	0.0508	-2.1297		
	Optical density, d		0.0309	/ metre	
	No of samples which ignited		4		
	For Samples which ignited				
	Smoke Release (Log D) - Mean		-2.1297		
	Smoke Release (Log D) - Standard Error		0.0508		
	No of samples which did not ignite		5		
	For Samples which did not ignite Smoke Release (Log D) - Mean		-1.5204		
	Smoke Release (Log D) - Standard Error		-1.5204		
	Number of specimens tested:		9		
			9		

236379

51162

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved Accredited for compliance with ISO/IEC 17025 - Testing

NATA

Page 1 of 2



Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

12





0204/11/06

C



Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

TEST REPORT

Client :	Kvadrat A/S Test Number		:	21-001965	
	Lundbergsvej 10	Issue Date	:	4/05/2021	
	Ebeltoft 8400	Print Date	:	6/05/2021	
	Denmark				
	Regulatory Indices:				
	Ignitability Index			9 Range 0-20	
	Spread of Flame Index			0 Range 0-10	

Heat Evolved Index

Smoke Developed Index

The reaction of thin unsupported flexible materials to flame impingement can be assessed in accordance with AS 1530.2. Where materials of thickness less than 2 mm that are sufficiently flexible to be bent by hand around a mandrel of 2mm diameter or less are subjected to the test described herein, they should also be subjected to the test in AS 1530.2.

Ignition is initiated by a pilot flame that is held near, but does not touch the specimen. A material that does not ignite during the standard test may ignite if contacted with a pilot flame during the test.

To allow free movement of sample during testing all corners were folded away from the clamps.

The specimens were mounted to simulate use in an unsupported or free hanging mode. The results may be significantly different when mounted to simulate a wall cladding or upholstery application.

Each test specimen was sandwiched between two layers of galvanised welded square mesh made from wire of nominal diameter 0.8mm and nominal spacing 12mm in both directions, stapled through at four points, each 100mm from the centre of the sample and the assembly clamped in four places.

These results only apply to the specimen mounted, as described in this report. The result of this fire test may be used to directly assess fire hazard, but it should be recognised that a single test method will not provide a full assessment of fire hazard under all fire conditions.

236379

51162

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

Fiona McDonald



0

2

Range 0-10

Range 0-10





C