Test Report

Report Number: 108184-3-PMI



DANISH TECHNOLOGICAL INSTITUTE

Gregersensvej 1 DK-2630 Taastrup +45 72 20 20 00 info@teknologisk.dk www.teknologisk.dk

Page 1 of 3 Init.: CHF/LELN Order no.: 108184 Encl.: 2

| Assignor: | Kvadrat A/S, Lundbergsvej 10, DK-8400 Ebeltoft |
|---------------|--|
| ltem: | Sample of upholstery fabric designated: Mountain |
| | Detailed information is given in enclosure A. |
| Sampling: | The assignor confirms having selected the product. The product was forwarded by the assignor and received at Danish Technological Institute on 9 November 2021. |
| Period: | The test took place from 16 November 2021 to 17 November 2021. |
| Method: | DS EN 1021-1:2014 Furniture-Assesment of the ignitability of upholstered furniture-Part 1: Ignition source of smouldering cigarette |
| Test results: | According to the criteria of ignition described in EN 1021-1, chapter 3, the result is: |
| | Non-ignition > PASSES |
| | The results are shown in enclosure A. |
| Terms: | This test was conducted accredited in accordance with international requirements (ISO/IEC 17025:2017) and in accordance with the General Terms and Conditions of Danish Technological Institute. The test results solely apply to the tested item. This test report may be quoted in extract only if Danish Technological Institute has granted its written consent. |
| Place: | Danish Technological Institute, Taastrup, Environmental Technology |
| Signature: | This document is only valid with a digital signature from Danish Technological Institute. The date of issue appears from the digital signature. |
| | Charlotte Fischer Senior Consultant |





Enclosure: A



Materials

Item: Sample of upholstery fabric designated: Mountain

| Combination of upholstered material tested: |
|--|
| Cover: |
| Designated Mountain |
| Fibre content: 100% polyester FR |
| Approximate mass per area: 279 g/m ² |
| Filling: Flame-retardant polyurethane foam designated, RP 37160. |
| Approximate density: 35 kg/m ³ |
| (Foam was provided by the test laboratory.) |

Results

| Test method: | DS EN 1021-1:2014 |
|-------------------------|--|
| Ignition source: | Smouldering cigarette |
| Water soaking: | Before testing the sample was not subjected to the water soaking and drying procedure described in EN 1021-1, annex D. |
| Conditioning atmosphere | e: 23±2 °C / 50±5 % RH |

Test result:

Non-ignition > PASSES

| | Cigarette Test No. | | |
|---|--------------------|----|----|
| Smouldering criteria | 1 | 2 | 3 |
| Unsafe escalating combustion (3.1.a) | No | No | No |
| Test assembly largely consumed (3.1.b) | No | No | No |
| Smoulders to extremities (3.1.c) | No | No | No |
| Smoulders through thickness (3.1.c) | No | No | No |
| Smoulders for more than 1 hour (3.1.d) | No | No | No |
| In final examination, presence of progressive smouldering (3.1.e) | No | No | No |
| Flaming criteria | | | |
| Occurrence of flames (3.2) | No | No | No |
| Self-extinguishing of the cigarettes before smouldering entire length | No | No | No |

The above test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

Enclosure: B



Photos

Test of: Sample of upholstery fabric designated: Mountain



Test Report

Report Number: 108184-4-PMI



DANISH TECHNOLOGICAL INSTITUTE

Gregersensvej 1 DK-2630 Taastrup +45 72 20 20 00 info@teknologisk.dk www.teknologisk.dk

Page 1 of 3 Init.: CHF/LELN Order no.: 108184 Encl.: 2

| Assignor: | Kvadrat A/S, Lundbergsvej 10, DK-8400 Ebeltoft |
|---------------|--|
| ltem: | Sample of upholstery fabric designated: Mountain |
| | Detailed information is given in enclosure A. |
| Sampling: | The assignor confirms having selected the product. The product was forwarded by the assignor and received at Danish Technological Institute on 9 November 2021. |
| Period: | The test took place from 16 November 2021 to 17 November 2021. |
| Method: | DS EN 1021-2:2014 Furniture- Assessment of the ignitability of upholstered funiture- Part 2: Ignition source match flame equivalent |
| Test results: | According to the criteria of ignition described in EN 1021-2, chapter 3, the result is: |
| | Non-ignition > PASSES |
| | The results are shown in enclosure A. |
| Terms: | This test was conducted accredited in accordance with international requirements (ISO/IEC 17025:2017) and in accordance with the General Terms and Conditions of Danish Technological Institute. The test results solely apply to the tested item. This test report may be quoted in extract only if Danish Technological Institute has granted its written consent. |
| Place: | Danish Technological Institute, Taastrup, Environmental Technology |
| Signature: | This document is only valid with a digital signature from Danish Technological Institute. The date of issue appears from the digital signature. |
| | Charlotte Fischer Senior Consultant |





Enclosure: A



Materials

Item: Sample of upholstery fabric designated: Mountain

Combination of upholstered material tested: Cover: Designated Mountain Fibre content: 100% polyester FR Approximate mass per area: 279 g/m² Filling: Flame-retardant polyurethane foam designated, RP 37160. Approximate density: 35 kg/m³ (Foam was provided by the test laboratory.)

Results

| Test method: | DS EN 1021-2:2014 |
|-------------------------|--|
| Ignition source: | Match flame equivalent |
| Water soaking: | Before testing the sample was not subjected to the water soaking and drying procedure described in EN 1021-2, annex D. |
| Conditioning atmosphere | : 23±2 °C / 50±5 % RH |

Test result: Non-ignition > PASSES

| | Test No. | | |
|---|----------|----|----|
| Smouldering criteria | 1 | 2 | 3 |
| Unsafe escalating combustion (3.1.a) | No | No | No |
| Test assembly consumed (3.1.b) | No | No | No |
| Smoulders to extremities (3.1.c) | No | No | No |
| Smoulders through thickness (3.1.c) | No | No | No |
| Smoulders for more than 1 hour (3.1.d) | No | No | No |
| In final examination, presence of progressive smouldering (3.1.e) | No | No | No |
| Flaming criteria | | | |
| Unsafe escalating combustion (3.2.a) | No | No | No |
| Test assembly consumed (3.2.b) | No | No | No |
| Flaming to extremities (3.2.c) | No | No | No |
| Flaming through thickness (3.2.c) | No | No | No |
| Flames longer than 120 s (3.2.d) | No | No | No |

The above test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

Enclosure: B



Photos

Test of: Sample of upholstery fabric designated: Mountain

